


September
2024



PRODUCT LINEUP

COMPANY INFORMATION

Company Name	i-PRO Co., Ltd.	Group Companies	Americas: i-PRO Americas Inc. Houston : 8550 Fallbrook Road, Suite 200, Houston, TX 77064, USA Anaheim : 2390 E. Orangewood Ave., Suite 490, Anaheim, CA 92806, USA Canada : 5750 Explorer Drive, Suite 101, Mississauga, Ontario, Canada
Established	2019	EMEA : i-PRO EMEA B.V.	Amsterdam: Laarderhoogtweg 25, 1101 EB Amsterdam, Netherlands
Representatives	Masato Nakao Shohei Ozaki	Asia Pacific: i-PRO APAC Pte. Ltd.	Singapore : 114 Lavender #01-36,51,52, CT Hub 2, Singapore 338729 Brisbane : 10/10 Depot Street, Banyo QLD, Australia 4014
Lines of Business	Development, manufacture and sales of devices and modules for the security, medicine and industrial fields. Providing solutions including system integration, construction, maintenance and related services.		
Number of Employees	Approx. 1400 (including group companies)		
Location Addresses	■ 2-15-1 Konan, Minato-ku, Tokyo, Japan ■ 7-9-66 Hakozaki, Higashi-ku, Fukuoka City, Fukuoka, Japan		



We strive to capture moments of underlying truth to better support the decisions of those professionals who protect and save lives, providing a safer and more peaceful world.

We have taken on this challenge to develop technological solutions that extend human senses with innovations that inform and protect, even in the most challenging environments.


We envision a future where it's possible to prevent unfortunate events. A future striking unmet medical conditions to improve the lives of millions of people.

We will be a trusted partner, focusing on the needs of our partners and customers to help create a safer and more peaceful world.

PRODUCT & TECHNOLOGY MILESTONES

i-PRO Co., Ltd., is a global leader of advanced sensing technologies in the fields of Intelligent Surveillance, Public Safety and Industrial/Medical Imaging. Established in 2019, i-PRO was built on a legacy of over 60 years of innovation with Panasonic.

The company's products, software and services extend human senses to capture moments of truth with innovations that inform and protect. In order to help create a safer world, i-PRO supports the work of professionals who protect and save lives.



CONTENTS

i-PRO CORE TECHNOLOGIES


Edge AI Technology	6
Open Platform	6
Cyber Security	7
Product Reliability	7
Reduced Bandwidth	8
Ease of Installation.....	8

i-PRO PRODUCTS

i-PRO Product Selector	9
i-PRO Camera Series Lineup.....	10
Multi-Sensor Cameras.....	15
Outdoor PTZ Cameras	16
Indoor PTZ Cameras.....	19
Outdoor Dome Cameras.....	20
Indoor Vandal Dome Cameras.....	21
Indoor Dome Cameras	22
Bullet Cameras.....	23
Box Cameras	26
Fisheye Cameras	26
Outdoor Compact Cameras.....	27
Indoor Compact Cameras.....	27
NVR WJ-NX310 / NX410 / NX510 Series	28
NVR with a build-in PoE+ switch	
WJ-NU101 / 201 / 300 / 301 Series.....	29
Management Software	30
i-PRO Mobile APP	30
Accessories.....	31
i-PRO Active Guard.....	32
Edge AI Analytics.....	33
System Design Tool	34
i-PRO Configuration Tool (iCT).....	34
Network Camera Model Number Format.....	35

SECURITY CAMERA ACCESSORY CHART

MULTI-DIRECTIONAL + PTZ CAMERAS	36
MULTI-SENSOR CAMERAS.....	36
DUAL-SENSOR CAMERAS	37
OUTDOOR PTZ CAMERAS	37/38/39/40
INDOOR PTZ CAMERAS	41
CORNER CAMERA.....	42
OUTDOOR DOME CAMERAS	42
INDOOR DOME CAMERAS.....	43
COMPACT DOME CAMERAS.....	43
HIGH ZOOM BULLET CAMERA /	
OUTDOOR BULLET CAMERAS	44
INDOOR BOX CAMERAS.....	45
OUTDOOR / INDOOR FISHEYE CAMERAS.....	45
COMPACT DOME CAMERAS.....	46
ON-VEHICLE CAMERA	46
INDOOR COMPACT CAMERA	46




■ EMEA
https://i-pro.com/products_and_solutions/eu-en/surveillance/solutions/technologies/ipro-core-technology

■ APAC
https://i-pro.com/products_and_solutions/apac-en/surveillance/solutions/technologies/ipro-core-technology

Edge AI Technology

i-PRO Edge AI Cameras

With powerful Edge AI processor at the edge, i-PRO network cameras can process advanced analytics locally and only send the lightweight results as metadata to the backend server.




Computer vision chip architecture

Collaborating with AI SoC company Ambarella, i-PRO network cameras have on-boarding advanced analytics technologies inside.




i-PRO Active Guard

i-PRO Active Guard is a time-saving search software which will help you to find out a specific objects quickly based on the metadata information from i-PRO Edge AI cameras.



Wide variety of Edge AI Cameras

i-PRO keeps expanding the product line-up of edge AI capable cameras since 2020 and it is growing to 238 models in 2024.



Open Platform

Integration with leading VMS

i-PRO network cameras are well integrated with leading VMS software, and i-PRO Active Guard integrated with in-house VMS Video Insight as well as Genetec Security Center and Milestone XProtect.




Integration with AI application partners

We will provide various AI applications developed in-house and developed by our global AI application partners.



Provides development support with free SDK/API

Free SDK/API and technical support is available for application partners.



Cyber Security

Built-in cyber security features

i-PRO cameras are designed and built with trust, safety, and security in mind. We take cyber security just as seriously as the lives and assets our products are made to protect. Our cameras include robust security features to meet the needs of customers who comply with security frameworks.



Pre-installed signed Certificates (GlobalSign®)

i-PRO was the first company in the security industry to provide a pre-installed signed certification by 3rd party certificate authority. Data is encrypted by SSL with pre-installed certified key and it will not allow any snooping and alteration.

FIPS 140-2 level 3 certified Secure Element

FIPS (Federal Information Processing Standards) are standards and guidelines for federal computer systems that are developed by NIST. Our latest models of i-PRO network cameras have equipped a Secure Element which is certified the FIPS 140-2 level 3 compliant.

NDAA compliant

i-PRO is proud to confirm that our products are compliant under the National Defense Authorization Act (NDAA). i-PRO doesn't use any manufactures, system on chips or any other components that have been banned under section 889 of the NDAA.




Product Reliability

IK10 Vandal resistant


Vandal resistant is one of the most important features of security cameras. IK10 rating indicates that the camera has a superior level of resistance against impact.

All i-PRO outdoor cameras comply the IK10 rating or more, which provides protection from physical damage.



ClearSight Coating

Our ClearSight coating enables to repel water drops on the dome cover in raining. This will provide you clear image in daytime and nighttime.



Anti-Condensation System

A built-in dehumidifier system avoids a condensation on the dome cover.



Salt damage resistant

Salt resistant models with special coating on the camera body and screws will work without a corrosion even in salt-air condition.



High durability mechanism for PTZ cameras

Pan/Tilt gear drive mechanism allows our i-PRO PTZ cameras to have longer life and more preciseness than a general belt-drive mechanism.



Built-in heater (Selected models)

Help to defrost snow or icicles on the camera even in extremely cold regions.



*Available only with special model

Reduced Bandwidth

AI Smart Coding

i-PRO Edge AI Cameras will detect people and vehicles and optimize the encoding parameters to reduce the bandwidth.




Bitrates of tree area are suppressed even it's swaying.

Bitrates of face and human area are maintained higher for high image quality.

Reduced Bandwidth

i-PRO Cameras' AI Smart coding supports up to 50% reduced bandwidth improvement.



Ease of Installation

Cameras designed for easier installation

i-PRO multi-sensor cameras are industry thinnest design and blends in seamlessly with environment. The hooking structure and light weight bring you an ease of installation.



Supports USB Wifi adapter (Selected models)

With Wifi USB dongle i-PRO cameras can be accessed via smartphone without connecting the camera to PC or analog monitor. The angle of view and the focus can be adjusted easily.

*Wifi USB dongle needs to be locally procured.



*WV-S71xxx, WV-S85xx

Easy kitting package


i-PRO easy kitting package is helpful for pre-configuration works. Cameras can be configured quickly without opening the box.



Installation Tools

i-PRO provides useful installation tools to support system design and configuration works easier and more efficient.

- Product Selector
- SDT (System Design Tool)
- ICT (i-PRO Configuration Tool)



i-PRO NETWORK PRODUCTS



Multi Sensor Cameras

i-PRO multi-sensor cameras capture the highest quality images even in very challenging dynamic environments. These cameras can excel at capturing clear images, even in low light conditions from multiple angles through the use of their four repositionable lenses.



PTZ Cameras

i-PRO PTZ cameras combine unparalleled image quality with incredible durability and reliability. The perfect security camera for wide-area coverage requiring pan, tilt and zoom capability.



Dome Cameras

i-PRO fixed dome cameras have the power to be more discreet than standard fixed network cameras. i-PRO fixed dome cameras work well in busy open areas since they can conceal which direction they are pointing while still providing excellent and reliable video.



Bullet/Box Cameras

i-PRO fixed box bullet/box cameras provide a clearly visible, fixed angle of view, making it easy to see exactly where they're pointing and record a precisely defined area.



360 Degree Cameras

i-PRO vandal resistant 360° dome cameras are ideal for surveillance applications where wide area coverage is required. This type of camera allows for multiple viewing angles and can be used to improve area management as well as detect activities in a large area.



Compact dome

Compact dome cameras with anti vibration and discreet design are suitable for installation in cars, buses, and other vehicles.



i-PRO mini

i-PRO mini provides powerful open AI technology in a compact format. It blends seamlessly into any surroundings and provides insights to solve a variety of problems. Extendable to marketing functions with third party AI apps.

i-PRO Product Selector

Overview

i-PRO releases Product Selector for both on Web and smartphone app. They are used to select the model by rich filters that meets your various needs from the i-PRO lineup of products.

Product Selector for Web

Product Selector for Web supports all categories of the i-PRO products. After selecting a product (camera or embedded recorder) that meets your requirements, you can easily select accessories needed for installation by simply setting the installation location by using the Accessory Selector.



Accessory Selector also provides a function that judges AI extension software compatibility and shows conditions and remarks.



Product Selector for Smartphone

This application can be used to select a network camera that meets your needs and accessories. And anyone can easily perform tasks from camera selection to proposal creation.

<https://i-pro.com/selector/product/>



i-PRO Camera Series Lineup

Series definition

X series eXtraordinary **S** series Standard **U** series Utility

Launch in 2024 Launch before 2023
With IR-LED With ClearSight Coating Salt damage resistant model

	Multi-Sensor	PTZ
X series	4 Multi-Directional+PTZ Camera Ai Outdoor 2MP 21xPTZ 4x5MP X86531-Z2 X86531-Z2-1 2MP 21xPTZ 3x5MP X86530-Z2 X86530-Z2-1	16 Aero PTZ Ai Outdoor 30x 4K X67711-Z3L3 X67710-Z3-3 X67710-Z3L3 X67710-Z3-1 X67710-Z3L1 30x 4K X67701-Z3L3 X67700-Z3-3 X67700-Z3L3 40x 2MP X67311-Z4L3 X67310-Z4-3 X67310-Z4L3 X67310-Z4-1 X67310-Z4L1 40x 2MP X67301-Z4L3 X67300-Z4-3 X67300-Z4L3
S series	20 AI Multi-Directional Camera Ai Outdoor Fix 2x4K S85702-F3L S85702-F3L1 (3.1mm) Vari 2x4MP S85402-V2L S85402-V2L1 Fix 4x4K S8574L S8574LG (3.1mm) Fix 3x4K S8573L S8573LG (3.1mm) Fix 4x6MP S8564L S8564LG (3.1mm) Fix 3x6MP S8563L S8563LG (3.1mm) Vari 4x4MP S8544L S8544LG S8544 S8544G Vari 3x4MP S8543L S8543LG S8543 S8543G	
U series	2 Multi-Directional Camera Outdoor Vari 2x4MP U85402-V2L U85402-V2L1	
TTL	26models	16

i-PRO Camera Series Lineup

Series definition

X series eXtraordinary **S** series Standard **U** series Utility

Launch in 2024 Launch before 2023
With IR-LED With ClearSight Coating Salt damage resistant model

	PTZ
X series	1 VCC (Vehicle Capture Camera) Global Shutter Tele 5MP X5550LT 4 Long Range IR PTZ Outdoor 40x 2MP X6533LN X6533LNS 22x 2MP S6532LN S6532LNS 16 AI Rapid-PTZ Camera Ai Outdoor 30x 4K X66700-Z3K X66700-Z3LK X66600-Z3K X66600-Z3LK 30x 4K X66700-Z3S X66700-Z3LS 30x 6MP X66600-Z3S X66600-Z3LS 40x 2MP X66300-Z4K X66300-Z4LK 32x 2MP X66300-Z3K X66300-Z3LK 40x 2MP X66300-Z4S X66300-Z4LS 32x 2MP X66300-Z3S X66300-Z3LS
S series	16 AI Rapid-PTZ Camera Ai Outdoor 30x 4K S66700-Z3N S66700-Z3LN 30x 6MP S66600-Z3N S66600-Z3LN 30x 4K S66700-Z3 S66700-Z3L 30x 6MP S66600-Z3 S66600-Z3L 40x 2MP S66300-Z4N S66300-Z4LN 32x 2MP S66300-Z3N S66300-Z3LN 40x 2MP S66300-Z4 S66300-Z4L 32x 2MP S66300-Z3 S66300-Z3L 29 AI PTZ Camera Ai Outdoor 40x 2MP S65340-Z4 S65340-Z4N S65340-Z4G S65340-Z4N1 S65340-Z4K 21x 2MP S65340-Z2 S65340-Z2N S65340-Z2G S65340-Z2N1 S65340-Z2K 21x 2MP S65302-Z2 S65302-Z2G S65302-Z2-1 10x 6MP S65501-Z1 S65501-Z1G 10x 2MP S65301-Z1 S65301-Z1G S65301-Z1-1 S65301-Z1S 3.1x 2MP S65300-ZY S65300-ZYG Indoor 30x 4K S61702-Z3 30x 6MP S61602-Z3 40x 2MP S61302-Z4 10x 5MP S61501-Z1 21x 2MP S61301-Z2 10x 2MP S61301-Z1 3.1x 2MP S61300-ZY S61300-ZYG
U series	10 PTZ Camera Outdoor 21x 2MP U65302-Z2 U65302-Z2G 10x 2MP U65301-Z1 U65301-Z1G 3.1x 2MP U65300-ZY U65300-ZYG Indoor 21x 2MP U61301-Z2 10x 2MP U61301-Z1 3.1x 2MP U61300-ZY U61300-ZYG
TTL	76

i-PRO Camera Series Lineup

Series definition

X series eXtraordinary **S** series Standard **U** series Utility

Launch in 2024 Launch before 2023
With IR-LED With ClearSight Coating Salt damage resistant model

Dome

1 Corner Camera **Ai**
Outdoor
Fix 5MP X25580-F2LN2

8 X-series AI Camera **Ai**
Outdoor
Vari 4K X25700-V2LN Vari 6MP X25600-V2LN Vari 5MP X25500-V3LN Vari 2MP X25300-V3LN
Indoor Vandal
Vari 4K X22700-V2L Vari 6MP X22600-V2L Vari 5MP X22500-V3L Vari 2MP X22300-V3L

41 High Resolution AI Camera **Ai**
Outdoor
Vari 4K S25700-V2L S25700-V2LN S25700-V2LG S25700-V2LN1 Vari 6MP S25600-V2L S25600-V2LN S25600-V2LG
Vari 5MP S25500-V3L S25500-V3LN S25500-V3LG S25500-V3LN1 Fix 5MP S25500-F3L (3.2mm) S25500-F6L (6.1mm)
Indoor Vandal
Vari 4K S22700-V2L S22700-V2LG S22700-V2L1 Vari 6MP S22600-V2L S22600-V2LG Vari 5MP S22500-V3L S22500-V3LG S22500-V3L1 Fix 5MP S22500-F3L (3.2mm) S22500-F6L (6.1mm)

2MP Fixed AI Camera **Ai**
Outdoor
Vari 2MP S2536LA S2536LGA S2536LGA S2536LNA Tele 2MP S2536LTNA S2536LTA
Indoor Vandal
Vari 2MP S2236LA S2236LA-B S2236LGA S2236LGA-B
Indoor
Vari 2MP S2136A S2136A-B S2136LA S2136LA-B S2136GA S2136GA-B Vari 2MP S2136LGA S2136LGA-B

9 U-series Camera
Outdoor
Fix 4MP U2540LA (3.2mm) Vari 4MP U2542LA
Indoor
Fix 4MP U2140LA (3.2mm) Vari 4MP U2142LA
Build-in Mic
Vari 2MP U21300-V2L U2132LA
Fix 2MP U2530LA (3.2mm) Vari 2MP U2532LA
Fix 2MP U2130LA (3.2mm)

TTL

59

i-PRO Camera Series Lineup

Series definition

X series eXtraordinary **S** series Standard **U** series Utility

Launch in 2024 Launch before 2023
With IR-LED With ClearSight Coating Salt damage resistant model

Bullet / Box

12 High Zoom Bullet Camera **Ai**
Outdoor
30x 4K X15701-Z3L X15701-Z3LN 10x 5MP X15502-Z1L X15502-Z1LN
30x 5MP X15501-Z3L X15501-Z3LN 10x 5MP X15501-Z1L X15501-Z1LN
10x 2MP X15302-Z1L X15302-Z1LN 10x 2MP X15301-Z1L X15301-Z1LN

8 X-series AI Camera **Ai**
Outdoor
Vari 4K X15700-V2L X15700-V2LN Vari 6MP X15600-V2L X15600-V2LN
Vari 5MP X15500-V3L X15500-V3LN Vari 2MP X15300-V3L X15300-V3LN

8 High Zoom Bullet Camera **Ai**
Outdoor
30x 4K S15701-Z3L S15701-Z3LN 30x 5MP S15501-Z3L S15501-Z3LN 10x 5MP S15501-Z1L S15501-Z1LN 10x 2MP S15301-Z1L S15301-Z1LN

11 High Resolution AI Camera **Ai**
Outdoor
Vari 4K S15700-V2L S15700-V2LN S15700-V2LK
Vari 6MP S15600-V2L S15600-V2LN Vari 5MP S15500-V3LN S15500-V3LK
Vari 5MP S15500-V3L S15500-V3LN1 Fix 5MP S15500-F3L (3.2mm) S15500-F6L (6.1mm)

8 2MP Fixed AI Camera **Ai**
Outdoor
Vari 2MP S1536LA S1536LA-B S1536LNA S1536LNA-B S1536LNSA
Tele 2MP S1536LTA S1536LTNA
Indoor
2MP S1136A

6 U-series Camera
Outdoor
Vari 4MP U1542LA
Indoor
Vari 4MP U1142A
Build-in Mic
Vari 2MP U11300-V2 U1132A
Vari 2MP U1532LA
Fix 2MP U1130A (3.2mm)

TTL

53

i-PRO Camera Series Lineup				
Series definition				
X eXtraordinary S Standard U Utility Launch in 2024 Launch before 2023 With IR-LED With ClearSight Coating Salt damage resistant model				
	Fisheye	Compact	mini	TTL
X series	2 Fisheye Camera Ai Outdoor Fix S4576LMA 12MP (1.4mm) Fix S4556LMA 5MP (0.84mm)	1 Onboard Camera Outdoor Fix SBV131M 2MP (1.95mm) 4 Compact Dome Camera Ai Outdoor Fix X35402-F2LM 4MP (2.4mm) Fix X35402-F2L 2MP (2.4mm) Fix X35302-F2LM 2MP (2.4mm) Fix X35302-F2L 2MP (2.4mm)		77 models
	4 AI Fisheye Camera Ai Outdoor Fix S4576LA 12MP (1.4mm) Fix S4556LA 5MP (0.84mm) Indoor Fix S4176A 12MP (1.4mm) Fix S4156A 5MP (0.84mm)	12 Compact Dome Camera Ai Outdoor Fix S35402-F2L 4MP (2.4mm) Fix S35402-F2LG 2MP (2.4mm) Fix S35402-F2L1 2MP (2.4mm) Fix S35302-F2L 2MP (2.4mm) Fix S35302-F2LG 2MP (2.4mm) Fix S35302-F2L1 2MP (2.4mm) Indoor Vandal Fix S32402-F2L 4MP (2.4mm) Fix S32402-F2LG 2MP (2.4mm) Fix S32402-F2L1 2MP (2.4mm) Fix S32302-F2L 2MP (2.4mm) Fix S32302-F2LG 2MP (2.4mm) Fix S32302-F2L1 2MP (2.4mm)	1 i-PRO mini Ai Fix S71300A-F3 2MP (3.2mm)	150
S series				
U series		8 Compact Dome Camera Outdoor Fix U35401-F2L 4MP (2.4mm) Fix U35401-F2LG 2MP (2.4mm) Fix U35301-F2L 2MP (2.4mm) Fix U35301-F2LG 2MP (2.4mm) Indoor Fix U31401-F2L 4MP (2.4mm) Fix U31401-F2LG 2MP (2.4mm) Fix U31301-F2L 2MP (2.4mm) Fix U31301-F2LG 2MP (2.4mm)		35
TTL	6	25	1	262

MULTI-SENSOR CAMERAS

MODEL#	WV-X86531-Z2 (Z2-1) WV-X86530-Z2 (Z2-1)	WV-S8574L (LG) WV-S8573L (LG)	WV-S8564L (LG) WV-S8563L (LG)	WV-S8544L (LG) WV-S8543L (LG)
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	PTZ: 2MP Multi: 5MP x4 WV-S86531 5MP x3 WV-S86530	8MP(4K) x4 WV-S8574L (LG) 8MP(4K) x3 WV-S8573L (LG)	6MP x4 WV-S8564L (LG) 6MP x3 WV-S8563L (LG)	4MP x4 WV-S8544L (LG) 4MP x3 WV-S8543L (LG)
Analytics (Max. # of AI apps installation)	Edge AI (6) / Auto tracking	Edge AI (4)	Edge AI (4)	Edge AI (4)
Sensor	PTZ: 1/2.8 CMOS Multi: 1/2.7 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.7 CMOS
Focal length / F-number	PTZ: 4.0 to 84.6 mm, F1.6 Multi: 3.2 mm, F2.0	3.1 mm, F1.44	3.1 mm, F1.44	2.9 to 7.3mm, F2.0
Optical Zoom	PTZ: 21x, Motorized Multi: -	—	—	2.5x, Motorized
Horizontal angle of view (16:9)	PTZ: 3.7° to 77° / Endless pan Multi: 97° / lens	108°/lens	108°/lens	43° to 100°/lens
Built-in IR-LED	—	40 m / 131 ft. 30 m / 99 ft. (LG)	40 m / 131 ft. 30 m / 99 ft. (LG)	20 m / 66 ft. 15 m / 49 ft. (LG)
Min. Illumination (Color / B&W)	PTZ: 0.011 lx / 0.006 lx Multi: 0.12 lx / 0.10 lx	0.084 lx / 0 lx	0.084 lx / 0 lx	0.21 lx / 0 lx
WDR [Dynamic Range]	PTZ: Yes [144dB] Multi: Yes [108dB]	Yes [120dB]	Yes [120dB]	Yes [108dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	PTZ: 60 fps Multi: 15 fps	15 fps	15 fps	30 fps
Audio (In / Out / Built-in MIC)	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —
External I/O	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	IP67, IP66 / IK10	IP67, IP66 / IK10	IP67, IP66 / IK10	IP67, IP66 / IK10
Operating Temperature	-40 °C to +55 °C / -40 °F to +131 °F (60W PoE/24V AC)	-40 °C to +60 °C -40 °F to +140 °F	-40 °C to +60 °C -40 °F to +140 °F	-40 °C to +60 °C -40 °F to +140 °F
Power Source / Consumption	PoE++ 35.6 W	PoE+ 25.4W	PoE+ 25.4W	PoE+ 25.4W
Other	FIPS 140-2 LV3 [*1], NEMA TS2, Black (Z2-1)	FIPS 140-2 LV3 [*1], NEMA TS2, Smoke dome (LG), Re-paintable	FIPS 140-2 LV3 [*1], NEMA TS2, Smoke dome (LG), Re-paintable	FIPS 140-2 LV3 [*1], NEMA TS2, Smoke dome (LG), Re-paintable
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS

MULTI-SENSOR CAMERAS

MODEL#	WV-S8544 (G) WV-S8543 (G)	WV-S85702-F3L (F3L1)	WV-S85402-V2L (V2L1)	WV-U85402-V2L (V2L1)
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	4MP x4 WV-S8544 (G) 4MP x3 WV-S8543 (G)	8MP(4K) x2	4MP x2	4MP x2
Analytics (Max. # of AI apps installation)	Edge AI (4)	Edge AI (4)	Edge AI (4)	VMD
Sensor	1/2.7 CMOS	1/2.8 CMOS	1/2.7 CMOS	1/2.7 CMOS
Focal length / F-number	2.9 to 7.3mm, F2.0	3.1 mm, F1.4	2.9 to 7.3 mm, F2.0	2.9 to 7.3 mm, F2.0
Optical Zoom	2.5x, Motorized	—	2.5x, Motorized	2.5x, Motorized
Horizontal angle of view (16:9)	43° to 100°/lens	104°/lens	43° to 100°/lens	43° to 100°/lens
Built-in IR-LED	—	40 m / 131 ft.	40 m / 131 ft.	40 m / 131 ft.
Min. Illumination (Color / B&W)	0.21 lx / 0.12 lx	0.084 lx / 0 lx	0.21 lx / 0 lx	0.21 lx / 0 lx
WDR [Dynamic Range]	Yes [108dB]	Yes [120dB]	Yes [108dB]	Yes [108dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	30 fps	15 fps	30 fps	30 fps
Audio (In / Out / Built-in MIC)	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —
External I/O	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	IP67, IP66 / IK10	IP67, IP66 / IK10	IP67, IP66 / IK10	IP67, IP66 / IK10
Operating Temperature	-40 °C to +60 °C -40 °F to +140 °F	-40 °C to +60 °C -40 °F to +140 °F	-40 °C to +60 °C -40 °F to +140 °F	-40 °C to +60 °C -40 °F to +140 °F
Power Source / Consumption	PoE+ 17.3W	PoE+ 18.9W	PoE+ 22.2W	PoE+ 18.9W
Other	FIPS 140-2 LV3 [*1], NEMA TS2, Smoke dome (G), Re-paintable	FIPS 140-2 LV3 [*1], Black (F3L1)	FIPS 140-2 LV3 [*1], Black (V2L1)	FIPS 140-2 LV3 [*1], Black (V2L1)
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS

[*1] FIPS 140-2 level 3-certified secure element is embedded. [*2] Option cable WV-QCA501A is needed.

OUTDOOR PTZ CAMERAS



COMING SOON



COMING SOON



COMING SOON



COMING SOON

MODEL#	WV-X67711-Z3L3	WV-X67710-Z3-3 (Z3L3) WV-X67710-Z3-1 (Z3L1)	WV-X67701-Z3L3	WV-X67700-Z3-3 (Z3L3)
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	8MP(4K)	8MP(4K)	8MP(4K)	8MP(4K)
Analytics (Max. # of AI apps installation)	Edge AI (3) / Auto tracking	Edge AI (3) / Auto tracking	Edge AI (3) / Auto tracking	Edge AI (3) / Auto tracking
Sensor	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	4.5 to 135 mm, F1.8	4.5 to 135 mm, F1.8	4.5 to 135 mm, F1.8	4.5 to 135 mm, F1.8
Optical Zoom	30x, Motorized	30x, Motorized	30x, Motorized	30x, Motorized
Horizontal angle of view (16:9)	2.5° to 62°	2.5° to 62°	2.5° to 62°	2.5° to 62°
Built-in IR-LED	160 m / 525 ft. *White LED Light	350 m / 1,148 ft. (Z3L3, Z3L1)	160 m / 525 ft. *White LED Light	350 m / 1,148 ft. (Z3L3)
Min. Illumination (Color / B&W)	0 lx / 0.1 lx	0.13 lx / 0.1 lx (Z3-3, Z3-1) 0.13 lx / 0 lx (Z3L3, Z3L1)	0 lx / 0.1 lx	0.13 lx / 0.1 lx (Z3-3) 0.13 lx / 0 lx (Z3L3)
WDR [Dynamic Range]	Yes [132dB]	Yes [132dB]	Yes [132dB]	Yes [132dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	30 fps	30 fps	30 fps	30 fps
Audio (In / Out / Built-in MIC)	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —
External I/O	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]
SD Memory Card Slot	—	—	—	—
Weather / Vandal Resistant	IP68, IP66 / IK10	IP68, IP66 / IK10	IP68, IP66 / IK10	IP68, IP66 / IK10
Operating Temperature	-50 °C to +65 °C -58 °F to +149 °F	-50°C to +65°C, -58°F to +149°F (Z3-3, Z3L3) -50°C to +60°C, -58°F to +140°F (Z3-1, Z3L1)	-50 °C to +65 °C -58 °F to +149 °F	-50 °C to +65 °C -58 °F to +149 °F
Power Source / Consumption	PoE++ / 24V AC 70W (PoE++ Class 8)	PoE++ / 24V AC 65W (PoE++ Class 8) (Z3-3, Z3-1) PoE++ / 24V AC 70W (PoE++ Class 8) (Z3L3, Z3L1)	PoE++ / 100-240V AC 70W (PoE++ Class 8)	PoE++ / 100-240V AC 65W (PoE++ Class 8) (Z3-3) PoE++ / 100-240V AC 70W (PoE++ Class 8) (Z3L3)
Other	FIPS 140-2 LV3 [*1], NEMA TS2, Salt resistant	FIPS 140-2 LV3 [*1], NEMA TS2, Salt resistant, Black (Z3-1, Z3L1)	FIPS 140-2 LV3 [*1], NEMA TS2, Salt resistant	FIPS 140-2 LV3 [*1], NEMA TS2, Salt resistant
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS

OUTDOOR PTZ CAMERAS



COMING SOON



COMING SOON



COMING SOON



COMING SOON

MODEL#	WV-X67311-Z4L3	WV-X67310-Z4-3 (Z4L3) WV-X67310-Z4-1 (Z4L1)	WV-X67301-Z4L3	WV-X67300-Z4-3 (Z4L3)
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	2MP	2MP	2MP	2MP
Analytics (Max. # of AI apps installation)	Edge AI (2) / Auto tracking	Edge AI (2) / Auto tracking	Edge AI (2) / Auto tracking	Edge AI (2) / Auto tracking
Sensor	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	4.25 to 170 mm, F1.6	4.25 to 170 mm, F1.6	4.25 to 170 mm, F1.6	4.25 to 170 mm, F1.6
Optical Zoom	40x, Motorized	40x, Motorized	40x, Motorized	40x, Motorized
Horizontal angle of view (16:9)	1.9° to 66°	1.9° to 66°	1.9° to 66°	1.9° to 66°
Built-in IR-LED	280 m / 918 ft. *White LED Light	560 m / 1,837 ft. (Z4L3, Z4L1)	280 m / 918 ft. *White LED Light	560 m / 1,837 ft. (Z4L3)
Min. Illumination (Color / B&W)	0 lx / 0.006 lx	0.011 lx / 0.006 lx (Z4-3, Z4-1) 0.011 lx / 0 lx (Z4L3, Z4L1)	0 lx / 0.006 lx	0.011 lx / 0.006 lx (Z4-3) 0.011 lx / 0 lx (Z4L3)
WDR [Dynamic Range]	Yes [144dB]	Yes [144dB]	Yes [144dB]	Yes [144dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	60 fps	60 fps	60 fps	60 fps
Audio (In / Out / Built-in MIC)	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —
External I/O	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]
SD Memory Card Slot	—	—	—	—
Weather / Vandal Resistant	IP68, IP66 / IK10	IP68, IP66 / IK10	IP68, IP66 / IK10	IP68, IP66 / IK10
Operating Temperature	-50 °C to +65 °C -58 °F to +149 °F	-50°C to +65°C -58°F to +149°F (Z4-3, Z4L3) -50°C to +60°C -58°F to +140°F (Z4-1, Z4L1)	-50 °C to +65 °C -58 °F to +149 °F	-50 °C to +65 °C -58 °F to +149 °F
Power Source / Consumption	PoE++ / 24V AC 70W (PoE++ Class 8)	PoE++ / 24V AC 65W (PoE++ Class 8) (Z4-3, Z4-1) PoE++ / 24V AC 70W (PoE++ Class 8) (Z4L3, Z4L1)	PoE++ / 100-240V AC 70W (PoE++ Class 8)	PoE++ / 100-240V AC 65W (PoE++ Class 8) (Z4-3) PoE++ / 100-240V AC 70W (PoE++ Class 8) (Z4L3)
Other	FIPS 140-2 LV3 [*1], NEMA TS2, Salt resistant	FIPS 140-2 LV3 [*1], NEMA TS2, Salt resistant, Black (Z4-1, Z4L1)	FIPS 140-2 LV3 [*1], NEMA TS2, Salt resistant	FIPS 140-2 LV3 [*1], NEMA TS2, Salt resistant
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS

[*1] FIPS 140-2 level 3-certified secure element is embedded. [*2] Option cable WV-QCA502 is needed.

OUTDOOR PTZ CAMERAS



MODEL#	WV-X66700-Z3S (Z3K)(Z3LS)(Z3LK) WV-S66700-Z3 (Z3N)(Z3L)(Z3LN)	WV-X66600-Z3S (Z3K)(Z3LS)(Z3LK) WV-S66600-Z3 (Z3N)(Z3L)(Z3LN)	WV-X66300-Z4S (Z4K)(Z4LS)(Z4LK) WV-S66300-Z4 (Z4N)(Z4L)(Z4LN)	WV-X66300-Z3S (Z3K)(Z3LS)(Z3LK) WV-S66300-Z3 (Z3N)(Z3L)(Z3LN)
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	4K	6MP	2MP	2MP
Analytics (Max. # of AI apps installation)	Edge AI (3) / Auto tracking	Edge AI (3) / Auto tracking	Edge AI (2) / Auto tracking	Edge AI (2) / Auto tracking
Sensor	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	4.5 to 135 mm, F1.8	4.5 to 135 mm, F1.8	4.25 to 170 mm, F1.6	4.25 to 136 mm, F1.6
Optical Zoom	30x, Motorized	30x, Motorized	40x, Motorized	32x, Motorized
Horizontal angle of view (16:9)	2.5° to 62° / Endless pan	2.5° to 62° / Endless pan	2.0° to 65° / Endless pan	2.4° to 65° / Endless pan
Built-in IR-LED	280 m / 920 ft. (Z3LS, Z3LK, Z3L, Z3LN)	280 m / 920 ft. (Z3LS, Z3LK, Z3L, Z3LN)	350 m / 1,148 ft. (Z4LS, Z4LK, Z4L, Z4LN)	350 m / 1,148 ft. (Z3LS, Z3LK, Z3L, Z3LN)
Min. Illumination (Color / B&W)	0.13 lx / 0 lx (Z3LS, Z3LK, Z3L, Z3LN) 0.13 lx / 0.1 lx (Z3S, Z3K, Z3, Z3N)	0.13 lx / 0 lx (Z3LS, Z3LK, Z3L, Z3LN) 0.13 lx / 0.1 lx (Z3S, Z3K, Z3, Z3N)	0.011 lx / 0 lx (Z4LS, Z4LK, Z4L, Z4LN) 0.011 lx / 0.006 lx (Z4S, Z4K, Z4, Z4N)	0.011 lx / 0 lx (Z3LS, Z3LK, Z3L, Z3LN) 0.011 lx / 0.006 lx (Z3S, Z3K, Z3, Z3N)
WDR [Dynamic Range]	Yes [132dB]	Yes [132dB]	Yes [144dB]	Yes [144dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	30 fps	30 fps	60 fps	60 fps
Audio (In / Out / Built-in MIC)	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —
External I/O	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	IP66 / IK10	IP66 / IK10	IP66 / IK10	IP66 / IK10
Operating Temperature	-50 °C to +60 °C -58°F to +140°F	-50 °C to +60 °C -58°F to +140°F	-50 °C to +60 °C -58°F to +140°F	-50 °C to +60 °C -58°F to +140°F
Power Source / Consumption	PoE++ 45.9 W (Z3LS, Z3LK, Z3L, Z3LN) 37.8 W (Z3S, Z3K, Z4, Z3N)	PoE++ 45.9 W (Z3LS, Z3LK, Z3L, Z3LN) 37.8 W (Z3S, Z3K, Z3, Z3N)	PoE++ 45.9 W (Z4LS, Z4LK, Z4L, Z4LN) 37.8 W (Z4S, Z4K, Z4, Z4N)	PoE++ 45.9 W (Z3LS, Z3LK, Z3L, Z3LN) 37.8 W (Z3S, Z3K, Z3, Z3N)
Other	FIPS 140-2 LV3 [*1], NEMA TS2, ClearSight(Z3K, Z3LK, Z3N, Z3LN), Salt resistant (X-series)	FIPS 140-2 LV3 [*1], NEMA TS2, ClearSight(Z3K, Z3LK, Z3N, Z3LN), Salt resistant (X-series)	FIPS 140-2 LV3 [*1], NEMA TS2, ClearSight(Z4K, Z4LK, Z4N, Z4LN), Salt resistant (X-series)	FIPS 140-2 LV3 [*1], NEMA TS2, ClearSight(Z3K, Z3LK, Z3N, Z3LN), Salt resistant (X-series)
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS

OUTDOOR PTZ CAMERAS



MODEL#	WV-X6533LN (LNS)	WV-S6532LN (LNS)	WV-S65340-Z4 (Z4N)(Z4G)(Z4N1)(Z4K)	WV-S65340-Z2 (Z2N)(Z2G)(Z2N1)(Z2K)
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	2MP	2MP	2MP	2MP
Analytics (Max. # of AI apps installation)	i-VMD / Auto tracking	i-VMD / Auto tracking	Edge AI (2) / Auto tracking	Edge AI (2) / Auto tracking
Sensor	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	4.25 to 170 mm, F1.6	4.25 to 95 mm, F1.6	4.25 to 170 mm, F1.6	4.0 to 84.6 mm, F1.6
Optical Zoom	40x, Motorized	22x, Motorized	40x, Motorized	21x, Motorized
Horizontal angle of view (16:9)	1.9° to 66° / Endless pan	3.4° to 66° / Endless pan	2.1° to 65° / Endless pan	3.7° to 17° / 0-350 Pan
Built-in IR-LED	350 m / 1,150 ft. (60W PoE/24V AC)	100 m / 330 ft.	—	—
Min. Illumination (Color / B&W)	0.015 lx / 0 lx	0.015 lx / 0 lx	0.015 lx / 0.006 lx	0.015 lx / 0.006 lx
WDR [Dynamic Range]	Yes [144dB]	Yes [144dB]	Yes [144dB]	Yes [144dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	60 fps	60 fps	60 fps	60 fps
Audio (In / Out / Built-in MIC)	Yes / Yes / —	Yes / Yes / —	Yes / Yes / —	Yes / Yes / —
External I/O	Yes	Yes	Yes	Yes
SD Memory Card Slot	SDXC	SDXC	microSDXC	microSDXC
Weather / Vandal Resistant	IP66 / IK10	IP66 / IK10	IP67, IP66 / IK10	IP67, IP66 / IK10
Operating Temperature	-50 °C to +60 °C / -58°F to +140°F (60W PoE/24V AC)	-40 °C to +60 °C / -40°F to +140°F (60W PoE/24V AC)	-50 °C to +60 °C / -58°F to +140°F (PoE++/24V AC)	-50 °C to +60 °C / -58°F to +140°F (PoE++/24V AC)
Power Source / Consumption	60W PoE / PoE+ / 24V AC 50W (60W PoE)	60W PoE / PoE+ / 24V AC 50W (60W PoE)	PoE++ / PoE+ / 24V AC 51W (PoE++)	PoE++ / PoE+ / 24V AC 51W (PoE++)
Other	ClearSight, Defroster, Salt resistant (LNS)	ClearSight, Defroster, Salt resistant (LNS)	FIPS 140-2 LV3 [*1], NEMA TS2, ClearSight (Z4N, Z4N1, Z4K), Smoke dome (Z4G), Black (Z4N1), Salt resistant (Z4K), Re-paintable	FIPS 140-2 LV3 [*1], NEMA TS2, ClearSight (Z2N, Z2N1, Z2K), Smoke dome (Z2G), Black (Z2N1), Salt resistant (Z2K), Re-paintable
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS

[*1] FIPS 140-2 level 3-certified secure element is embedded. [*2] Option cable WV-QCA501A is needed.

OUTDOOR
PTZ
CAMERAS



MODEL#	WV-S65501-Z1 (Z1G)	WV-S65302-Z2 (Z2G) (Z2-1)	WV-S65301-Z1 (Z1G) (Z1-1) (Z1S)	WV-S65300-ZY (ZYG)
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	5MP	2MP	2MP	2MP
Analytics (Max. # of AI apps installation)	Edge AI (3) / Auto tracking	Edge AI (2) / Auto tracking	Edge AI (2) / Auto tracking	Edge AI (2) / Auto tracking
Sensor	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	4.7 to 47.0 mm, F1.6	4.0 to 84.6 mm, F1.6	4.7 to 47.0 mm, F1.6	2.9 to 9 mm, F1.3
Optical Zoom	10x, Motorized	21x, Motorized	10x, Motorized	3.1x, Motorized
Horizontal angle of view (16:9)	6° to 57° / Endless pan	3.7° to 77° / Endless pan	6.7° to 62° / Endless pan	36° to 113° / 0-350 pan
Built-in IR-LED	—	—	—	—
Min. Illumination (Color / B&W)	0.11 lx / 0.006 lx	0.015 lx / 0.006 lx	0.015 lx / 0.006 lx	0.01 lx / 0.004 lx
WDR [Dynamic Range]	Yes [132dB]	Yes [144dB]	Yes [144dB]	Yes [144dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	60 fps	60 fps	60 fps	60 fps
Audio (In / Out / Built-in MIC)	Yes / Yes[*2] / —	Yes / Yes[*2] / —	Yes / Yes[*2] / —	Yes / Yes[*2] / —
External I/O	Yes[*2]	Yes[*2]	Yes[*2]	Yes[*2]
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	IP66 / IK10	IP66 / IK10	IP66 / IK10	IP66 / IK10
Operating Temperature	-30 °C to +55 °C -22°F to +131°F	-30 °C to +55 °C -22°F to +131°F	-30 °C to +55 °C -22°F to +131°F	-30 °C to +55 °C -22°F to +131°F
Power Source / Consumption	PoE+ / 12V DC[*2] 18.4W (PoE+)	PoE+ / 12V DC[*2] 18.4W (PoE+)	PoE+ / 12V DC[*2] 18.4W (PoE+)	PoE / 12V DC[*2] 12W (PoE)
Other	FIPS 140-2 LV3 [*1], NEMA TS2, Smoke dome (Z1G), Re-paintable	FIPS 140-2 LV3 [*1], NEMA TS2, Smoke dome (Z2G), Black (Z2-1), Re-paintable	FIPS 140-2 LV3 [*1], NEMA TS2, Smoke dome (Z1G), Black (Z1-1), Salt resistant (Z1S), Re-paintable	FIPS 140-2 LV3 [*1], NEMA TS2, Smoke dome (ZYG), Re-paintable
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS

OUTDOOR
PTZ
CAMERAS



MODEL#	WV-U65302-Z2 (Z2G)	WV-U65301-Z1 (Z1G)	WV-U65300-ZY (ZYG)
Environmental Type	Outdoor	Outdoor	Outdoor
Resolution	2MP	2MP	2MP
Analytics (Max. # of AI apps installation)	VMD	VMD	VMD
Sensor	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	4.0 to 84.6 mm, F1.6	4.7 to 47.0 mm, F1.6	2.9 to 9 mm, F1.3
Optical Zoom	21x, Motorized	10x, Motorized	3.1x, Motorized
Horizontal angle of view (16:9)	3.7° to 77° / Endless pan	6.7° to 62° / Endless pan	36° to 113° / 0-350 pan
Built-in IR-LED	—	—	—
Min. Illumination (Color / B&W)	0.015 lx / 0.006 lx	0.015 lx / 0.006 lx	0.01 lx / 0.004 lx
WDR [Dynamic Range]	Yes [144dB]	Yes [144dB]	Yes [144dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	60 fps	60 fps	60 fps
Audio (In / Out / Built-in MIC)	Yes / Yes[*2] / —	Yes / Yes[*2] / —	Yes / Yes[*2] / —
External I/O	Yes[*2]	Yes[*2]	Yes[*2]
SD Memory Card Slot	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	IP66 / IK10	IP66 / IK10	IP66 / IK10
Operating Temperature	-30 °C to +55 °C -22°F to +131°F	-30 °C to +55 °C -22°F to +131°F	-30 °C to +55 °C -22°F to +131°F
Power Source / Consumption	PoE+ / 12V DC[*2] 18.4W (PoE+)	PoE+ / 12V DC[*2] 18.4W (PoE+)	PoE / 12V DC[*2] 12W (PoE)
Other	FIPS 140-2 LV3 [*1], NEMA TS2, Smoke dome (Z2G), Re-paintable	FIPS 140-2 LV3 [*1], NEMA TS2, Smoke dome (Z1G), Re-paintable	FIPS 140-2 LV3 [*1], NEMA TS2, Smoke dome (ZYG), Re-paintable
Bracket Chart	BRACKETS	BRACKETS	BRACKETS

[*1] FIPS 140-2 level 3-certified secure element is embedded. [*2] Option cable WV-QCA501A is needed.

INDOOR
PTZ
CAMERAS



COMING SOON



COMING SOON



MODEL#	WV-S61702-Z3	WV-S61602-Z3	WV-S61302-Z4	WV-S61501-Z1	WV-S61301-Z2 WV-U61301-Z2
Environmental Type	Indoor	Indoor	Indoor	Indoor	Indoor
Resolution	8MP (4K)	6MP	2MP	5MP	2MP
Analytics (Max. # of AI apps installation)	Edge AI (3)	Edge AI (3)	Edge AI (2) / Auto tracking	Edge AI (3) / Auto tracking	Edge AI (2) / Auto tracking (S-series), VMD(U-series)
Sensor	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	4.5 to 135 mm, F1.8	4.5 to 135 mm, F1.8	4.25 to 170 mm, F1.6	4.7 to 47.0 mm, F1.6	4.0 to 84.6 mm, F1.6
Optical Zoom	30x, Motorized	30x, Motorized	40x, Motorized	10x, Motorized	21x, Motorized
Horizontal angle of view (16:9)	2.5° to 62°	2.5° to 62°	1.9° to 66° / Endless pan	6° to 57° / 0-350 pan	3.7° to 77° / 0-350 Pan
Built-in IR-LED	—	—	—	—	—
Min. Illumination (Color / B&W)	0.13 lx / 0.1lx	0.13 lx / 0.1lx	0.015 lx / 0.006 lx	0.11 lx / 0.06 lx	0.015 lx / 0.006 lx
WDR [Dynamic Range]	Yes [132dB]	Yes [132dB]	Yes [144dB]	Yes [132dB]	Yes [144dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	30 fps	30 fps	60 fps	30 fps	60 fps
Audio (In / Out / Built-in MIC)	Yes / Yes / —	Yes / Yes / —	Yes / Yes / —	Yes / Yes / —	Yes / Yes / —
External I/O	Yes	Yes	Yes	Yes	Yes
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	— / —	— / —	— / —	— / —	— / —
Operating Temperature	-10°C to +50°C +14°F to +122°F	-10°C to +50°C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F
Power Source / Consumption	PoE+ / 12V DC 16.7W (PoE+)	PoE+ / 12V DC 16.7W (PoE+)	PoE / 12V DC 12.95W (PoE)	PoE / 12V DC 12.95W (PoE)	PoE / 12V DC 12.95W (PoE)
Other	FIPS 140-2 LV3 [*1]	FIPS 140-2 LV3 [*1]	FIPS 140-2 LV3 [*1]	FIPS 140-2 LV3 [*1]	FIPS 140-2 LV3 [*1]
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS	BRACKETS

INDOOR
PTZ
CAMERAS



MODEL#	WV-S61301-Z1	WV-S61300-ZY (ZYG)	WV-U61301-Z1	WV-U61300-ZY (ZYG)
Environmental Type	Indoor	Indoor	Indoor	Indoor
Resolution	2MP	2MP	2MP	2MP
Analytics (Max. # of AI apps installation)	Edge AI (2) / Auto tracking	Edge AI (2) / Auto tracking	VMD	VMD
Sensor	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	4.7 to 47.0 mm, F1.6	2.9 to 9 mm, F1.3	4.7 to 47.0 mm, F1.6	2.9 to 9 mm, F1.3
Optical Zoom	10x, Motorized	3.1x, Motorized	10x, Motorized	3.1x, Motorized
Horizontal angle of view (16:9)	6.7° to 62° / 0-350 pan	36° to 115° / 0-350 pan	6.7° to 62° / 0-350 pan	36° to 115° / 0-350 pan
Built-in IR-LED	—	—	—	—
Min. Illumination (Color / B&W)	0.015 lx / 0.006 lx	0.01 lx / 0.004 lx	0.015 lx / 0.006 lx	0.01 lx / 0.004 lx
WDR [Dynamic Range]	Yes [144dB]	Yes [144dB]	Yes [144dB]	Yes [144dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	60 fps	60 fps	60 fps	60 fps
Audio (In / Out / Built-in MIC)	Yes / Yes / —	Yes / Yes / —	Yes / Yes / —	Yes / Yes / —
External I/O	Yes	Yes	Yes	Yes
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	— / —	— / —	— / —	— / —
Operating Temperature	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F
Power Source / Consumption	PoE / 12V DC 12.95W (PoE)	PoE / 12V DC 12W (PoE)	PoE / 12V DC 12.95W (PoE)	PoE / 12V DC 12W (PoE)
Other	FIPS 140-2 LV3 [*1]	FIPS 140-2 LV3 [*1], Smoke dome (ZYG)	FIPS 140-2 LV3 [*1]	FIPS 140-2 LV3 [*1], Smoke dome (ZYG)
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS

[*1] FIPS 140-2 level 3-certified secure element is embedded.

OUTDOOR
DOME
CAMERAS



MODEL#	WV-X25580-F2LN2	WV-X25700-V2LN	WV-X25600-V2LN	WV-X25500-V3LN	WV-X25300-V3LN
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	5MP	8MP(4K)	6MP	5MP	2MP
Analytics (Max. # of AI apps installation)	Edge AI (3)	Edge AI (9) / AI relay / On-site learning	Edge AI (9) / AI relay / On-site learning	Edge AI (9) / AI relay / On-site learning	Edge AI (9) / AI relay / On-site learning
Sensor	1/2.8 CMOS	1/1.8 CMOS	1/1.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	2.3 mm, F2.2	4.3 to 8.6 mm, F1.5	4.3 to 8.6 mm, F1.5	2.9 to 9 mm, F1.3	2.9 to 9 mm, F1.3
Optical Zoom	—	2x, Motorized	2x, Motorized	3.1x, Motorized	3.1x, Motorized
Horizontal angle of view (16:9)	131°	52° to 101°	52° to 101°	33° to 103°	36° to 113°
Built-in IR-LED	21 m / 69 ft.	70 m / 230 ft.	70 m / 230 ft.	70 m / 230 ft.	70 m / 230 ft.
Min. Illumination (Color / B&W)	0.08 lx / 0 lx	0.04 lx / 0 lx	0.04 lx / 0 lx	0.03 lx / 0 lx	0.007 lx / 0 lx
WDR [Dynamic Range]	Yes [132dB]	Yes [132dB]	Yes [132dB]	Yes [132dB]	Yes [144dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	30 fps	60 fps	60 fps	60 fps	60 fps
Audio (In / Out / Built-in MIC)	Yes[*2] / Yes[*2] / Yes	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —
External I/O	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	IP69, IP67, IP66 / IK11, 70J IP6K9K	IP67, IP66 / IK10, 50J	IP67, IP66 / IK10, 50J	IP67, IP66 / IK10, 50J	IP67, IP66 / IK10, 50J
Operating Temperature	-40 °C to +55 °C -40 °F to +131 °F	-40 °C to +55 °C -40°F to +131°F	-40 °C to +55 °C -40°F to +131°F	-40 °C to +55 °C -40°F to +131°F	-40 °C to +55 °C -40°F to +131°F
Power Source / Consumption	PoE / 12V DC 11.5W (PoE)	PoE+ / 12V DC [*2] 14.0W (PoE+)	PoE+ / 12V DC [*2] 14.0W (PoE+)	PoE+ / 12V DC [*2] 14.0W (PoE+)	PoE+ / 12V DC [*2] 14.0W (PoE+)
Other	FIPS 140-2 LV3 [*1], ClearSight,	FIPS 140-2 LV3 [*1], ClearSight, Re-paintable	FIPS 140-2 LV3 [*1], ClearSight, Re-paintable	FIPS 140-2 LV3 [*1], ClearSight, Re-paintable	FIPS 140-2 LV3 [*1], ClearSight, Re-paintable
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS	BRACKETS

OUTDOOR
DOME
CAMERAS



MODEL#	WV-S25700-V2L (V2LN)(V2LG)(V2LN1)	WV-S25600-V2L (V2LN)(V2LG)	WV-S25500-V3L (V3LN)(V3LG)(V3LN1)	WV-S25500-F6L	WV-S25500-F3L
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	8MP(4K)	6MP	5MP	5MP	5MP
Analytics (Max. # of AI apps installation)	Edge AI (3)	Edge AI (3)	Edge AI (3)	Edge AI (3)	Edge AI (3)
Sensor	1/1.8 CMOS	1/1.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	4.3 to 8.6 mm, F1.5	4.3 to 8.6 mm, F1.5	2.9 to 9 mm, F1.3	6.1 mm, F1.6	3.2 mm, F2.0
Optical Zoom	2x, Motorized	2x, Motorized	3.1x, Motorized	—	—
Horizontal angle of view (16:9)	52° to 101°	52° to 101°	33° to 103°	48°	95°
Built-in IR-LED	70 m / 230 ft. 45 m / 148 ft. (V2LG)	70 m / 230 ft. 45 m / 148 ft. (V2LG)	55 m / 180 ft. 35 m / 115 ft. (V3LG)	45 m / 148 ft.	35 m / 115 ft.
Min. Illumination (Color / B&W)	0.04 lx / 0 lx	0.04 lx / 0 lx	0.05 lx / 0 lx	0.08 lx / 0 lx	0.12 lx / 0 lx
WDR [Dynamic Range]	Yes [132dB]	Yes [132dB]	Yes [132dB]	Yes [132dB]	Yes [132dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	30 fps	30 fps	30 fps	30 fps	30 fps
Audio (In / Out / Built-in MIC)	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —
External I/O	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	IP66 / IK10, 50J	IP66 / IK10, 50J	IP66 / IK10, 50J	IP66 / IK10, 50J	IP66 / IK10, 50J
Operating Temperature	-40 °C to +60 °C -40°F to +140°F	-40 °C to +60 °C -40°F to +140°F	-40 °C to +60 °C -40°F to +140°F	-40 °C to +60 °C -40°F to +140°F	-40 °C to +60 °C -40°F to +140°F
Power Source / Consumption	PoE / 12V DC [*2] 11.5W (PoE)	PoE / 12V DC [*2] 11.5W (PoE)	PoE / 12V DC [*2] 11.5W (PoE)	PoE / 12V DC [*2] 10.6W (PoE)	PoE / 12V DC [*2] 10.6W (PoE)
Other	FIPS 140-2 LV3 [*1], ClearSight (V2LN) (V2LN1), Smoke dome (V2LG), Black (V2LN1), Re-paintable	FIPS 140-2 LV3 [*1], ClearSight (V2LN), Smoke dome (V2LG), Re-paintable	FIPS 140-2 LV3 [*1], ClearSight (V3LN) (V3LN1), Smoke dome (V3LG), Black (V3LN1), Re-paintable	FIPS 140-2 LV3 [*1], Re-paintable	FIPS 140-2 LV3 [*1], Re-paintable
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS	BRACKETS

[*1] FIPS 140-2 level 3-certified secure element is embedded. [*2] Option cable WV-QCA501A is needed.

OUTDOOR
DOME
CAMERAS



MODEL#	WV-S2536LA (LNA)(LGA)(LGNA)	WV-S2536LTA (LTNA)	WV-U2542LA	WV-U2540LA	WV-U2532LA	WV-U2530LA
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	2MP	2MP	4MP	4MP	2MP	2MP
Analytics (Max. # of AI apps installation)	Edge AI (2)	Edge AI (2)	VMD	VMD	VMD	VMD
Sensor	1/2.8 MOS	1/2.8 MOS	1/2.7 CMOS	1/2.7 CMOS	1/3 CMOS	1/3 CMOS
Focal length / F-number	2.9 to 9mm, F1.3	9 to 21mm, F1.7	2.9 to 7.3 mm, F2.0	3.2 mm, F2.0	2.9 to 7.3 mm, F2.0	3.2 mm, F2.0
Optical Zoom	3.1x, Motorized	2.3x, Motorized	2.5x, Motorized	—	2.5x, Motorized	—
Horizontal angle of view (16:9)	36° to 113°	15° to 36°	43° to 100°	100°	42° to 97°	97°
Built-in IR-LED	70 m / 230 ft. 50 m / 164 ft. (LGA, LGNA)	70 m / 230 ft.	20 m / 65 ft.	20 m / 65 ft.	30 m / 98 ft.	30 m / 98 ft.
Min. Illumination (Color / B&W)	0.007 lx / 0 lx	0.011 lx / 0 lx	0.3 lx / 0 lx	0.3 lx / 0 lx	0.1 lx / 0 lx	0.1 lx / 0 lx
WDR [Dynamic Range]	Yes [144dB]	Yes [144dB]	Yes [102dB]	Yes [102dB]	Yes [120dB]	Yes [120dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	60 fps	60 fps	30 fps	30 fps	30 fps	30 fps
Audio (In / Out / Built-in MIC)	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	— / — / —	— / — / —	— / — / —	— / — / —
External I/O	Yes [*2]	Yes [*2]	—	—	—	—
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	IP66 / IK10, 50J	IP66 / IK10, 50J	IP66 / IK10	IP66 / IK10	IP66 / IK10	IP66 / IK10
Operating Temperature	-40 °C to +60 °C -40°F to +140°F	-40 °C to +60 °C -40°F to +140°F	-30 °C to +50 °C -22°F to +122°F	-30 °C to +50 °C -22°F to +122°F	-30 °C to +50 °C -22°F to +122°F	-30 °C to +50 °C -22°F to +122°F
Power Source / Consumption	PoE / 12V DC [*2] 9.1W (PoE)	PoE / 12V DC [*2] 10.1W (PoE)	PoE 7.2W	PoE 5.3W	PoE 6.7W	PoE 4.8W
Other	FIPS 140-2 LV3 [*1], ClearSight (LNA) (LGNA), Smoke dome (LGA) (LGNA), Re-paintable	FIPS 140-2 LV3 [*1], ClearSight (LTNA), Re-paintable	—	—	—	—
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS	BRACKETS	BRACKETS

INDOOR
VANDAL
DOME
CAMERAS



MODEL#	WV-X22700-V2L	WV-X22600-V2L	WV-X22500-V3L	WV-X22300-V3L
Environmental Type	Indoor Vandal	Indoor Vandal	Indoor Vandal	Indoor Vandal
Resolution	8MP(4K)	6MP	5MP	2MP
Analytics (Max. # of AI apps installation)	Edge AI (9) / AI relay / On-site learning	Edge AI (9) / AI relay / On-site learning	Edge AI (9) / AI relay / On-site learning	Edge AI (9) / AI relay / On-site learning
Sensor	1/1.8 CMOS	1/1.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	4.3 to 8.6 mm, F1.5	4.3 to 8.6 mm, F1.5	2.9 to 9 mm, F1.3	2.9 to 9 mm, F1.3
Optical Zoom	2x, Motorized	2x, Motorized	3.1x, Motorized	3.1x, Motorized
Horizontal angle of view (16:9)	52° to 101°	52° to 101°	33° to 105°	36° to 114°
Built-in IR-LED	70 m / 230 ft.	70 m / 230 ft.	70 m / 230 ft.	70 m / 230 ft.
Min. Illumination (Color / B&W)	0.04 lx / 0 lx	0.04 lx / 0 lx	0.03 lx / 0 lx	0.007 lx / 0 lx
WDR [Dynamic Range]	Yes [132dB]	Yes [132dB]	Yes [132dB]	Yes [144dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	60 fps	60 fps	60 fps	60 fps
Audio (In / Out / Built-in MIC)	Yes / Yes / —	Yes / Yes / —	Yes / Yes / —	Yes / Yes / —
External I/O	Yes	Yes	Yes	Yes
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	— / IK10	— / IK10	— / IK10	— / IK10
Operating Temperature	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F
Power Source / Consumption	PoE+ / 12V DC 14.0W (PoE+)	PoE+ / 12V DC 14.0W (PoE+)	PoE+ / 12V DC 14.0W (PoE+)	PoE+ / 12V DC 14.0W (PoE+)
Other	FIPS 140-2 LV3 [*1], Re-paintable	FIPS 140-2 LV3 [*1], Re-paintable	FIPS 140-2 LV3 [*1], Re-paintable	FIPS 140-2 LV3 [*1], Re-paintable
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS

[*1] FIPS 140-2 level 3-certified secure element is embedded. [*2] Option cable WV-QCA501A is needed.

INDOOR
VANDAL
DOME
CAMERAS



MODEL#	WV-S22700-V2L (V2LG) (V2L1)	WV-S22600-V2L (V2LG)	WV-S22500-V3L (V3LG) (V3L1)	WV-S22500-F6L
Environmental Type	Indoor Vandal	Indoor Vandal	Indoor Vandal	Indoor Vandal
Resolution	8MP(4K)	6MP	5MP	5MP
Analytics (Max. # of AI apps installation)	Edge AI (3)	Edge AI (3)	Edge AI (3)	Edge AI (3)
Sensor	1/1.8 CMOS	1/1.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	4.3 to 8.6 mm, F1.5	4.3 to 8.6 mm, F1.5	2.9 to 9 mm, F1.3	6.1 mm, F1.6
Optical Zoom	2x, Motorized	2x, Motorized	3.1x, Motorized	—
Horizontal angle of view (16:9)	52° to 101°	52° to 101°	33° to 105°	48°
Built-in IR-LED	50 m / 164 ft. 35 m / 115 ft. (V2LG)	50 m / 164 ft. 35 m / 115 ft. (V2LG)	40 m / 131 ft. 25 m / 82 ft. (V3LG)	35 m / 115 ft.
Min. Illumination (Color / B&W)	0.04 lx / 0 lx	0.04 lx / 0 lx	0.05 lx / 0 lx	0.08 lx / 0 lx
WDR [Dynamic Range]	Yes [132dB]	Yes [132dB]	Yes [132dB]	Yes [132dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	30 fps	30 fps	30 fps	30 fps
Audio (In / Out / Built-in MIC)	Yes / Yes / —	Yes / Yes / —	Yes / Yes / —	Yes / Yes / —
External I/O	Yes	Yes	Yes	Yes
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	— / IK10	— / IK10	— / IK10	— / IK10
Operating Temperature	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F
Power Source / Consumption	PoE / 12V DC 11.5W (PoE)	PoE / 12V DC 11.5W (PoE)	PoE / 12V DC 11.5W (PoE)	PoE / 12V DC 10.6W (PoE)
Other	FIPS 140-2 LV3 [*1], Smoke dome (V2LG), Black (V2L1), Re-paintable	FIPS 140-2 LV3 [*1], Smoke dome (V2LG), Re-paintable	FIPS 140-2 LV3 [*1], Smoke dome (V3LG), Black (V3L1), Re-paintable	FIPS 140-2 LV3 [*1], Re-paintable
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS

INDOOR
DOME
CAMERAS



MODEL#	WV-S22500-F3L	WV-S2236LA (LGA)(LA-B)(LGA-B)	WV-S2136LA (LGA)(LA-B)(LGA-B)	WV-S2136A (-B)(GA)(GA-B)
Environmental Type	Indoor Vandal	Indoor Vandal	Indoor	Indoor
Resolution	5MP	2MP	2MP	2MP
Analytics (Max. # of AI apps installation)	Edge AI (3)	Edge AI (2)	Edge AI (2)	Edge AI (2)
Sensor	1/2.8 CMOS	1/2.8 MOS	1/2.8 MOS	1/2.8 MOS
Focal length / F-number	3.2 mm, F2.0	2.9 to 9 mm, F1.3	2.9 to 9 mm, F1.3	2.9 to 9 mm, F1.3
Optical Zoom	—	3.1x, Motorized	3.1x, Motorized	3.1x, Motorized
Horizontal angle of view (16:9)	95°	36° to 114°	36° to 115°	36° to 115°
Built-in IR-LED	25 m / 82 ft.	70 m / 230 ft. 50 m / 164 ft. (LGA, LGA-B)	70 m / 230 ft. 50 m / 164 ft. (LGA, LGA-B)	—
Min. Illumination (Color / B&W)	0.12 lx / 0 lx	0.007 lx / 0 lx	0.007 lx / 0 lx	0.007 lx / 0.006 lx
WDR [Dynamic Range]	Yes [132dB]	Yes [144dB]	Yes [144dB]	Yes [144dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	30 fps	60 fps	60 fps	60 fps
Audio (In / Out / Built-in MIC)	Yes / Yes / —	Yes / Yes / —	Yes / Yes / —	Yes / Yes / —
External I/O	Yes	Yes	Yes	Yes
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	— / IK10	— / IK10	— / —	— / —
Operating Temperature	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F
Power Source / Consumption	PoE / 12V DC 10.6W (PoE)	PoE / 12V DC 8.7W (PoE)	PoE / 12V DC 8.7W (PoE)	PoE / 12V DC 8.7W (PoE)
Other	FIPS 140-2 LV3 [*1], Re-paintable	FIPS 140-2 LV3 [*1], Smoke dome (LGA) (LGA-B), Black (LA-B) (LGA-B), Re-paintable	FIPS 140-2 LV3 [*1], Smoke dome (LGA) (LGA-B), Black (LA-B) (LGA-B)	FIPS 140-2 LV3 [*1], Smoke dome (GA) (GA-B), Black (-B) (GA-B)
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS

[*1] FIPS 140-2 level 3-certified secure element is embedded.

INDOOR
DOME
CAMERAS



MODEL#	WV-U2142LA	WV-U2140LA	WV-U21300-V2L	WV-U2132LA	WV-U2130LA
Environmental Type	Indoor	Indoor	Indoor	Indoor	Indoor
Resolution	4MP	4MP	2MP	2MP	2MP
Analytics (Max. # of AI apps installation)	VMD	VMD	VMD	VMD	VMD
Sensor	1/2.7 CMOS	1/2.7 CMOS	1/2.8 CMOS	1/3 CMOS	1/3 CMOS
Focal length / F-number	2.9 to 7.3 mm, F2.0	3.2 mm, F2.0	2.9 to 7.3 mm, F2.0	2.9 to 7.3 mm, F2.0	3.16 mm, F2.0
Optical Zoom	2.5x, Motorized	—	2.5x, Motorized	2.5x, Motorized	—
Horizontal angle of view (16:9)	44° to 102°	100°	42° to 97°	42° to 97°	97°
Built-in IR-LED	20 m / 65 ft.	20 m / 65 ft.	40 m / 131 ft.	40 m / 131 ft.	30 m / 98 ft.
Min. Illumination (Color / B&W)	0.3 lx / 0 lx	0.3 lx / 0 lx	0.1 lx / 0 lx	0.1 lx / 0 lx	0.1 lx / 0 lx
WDR [Dynamic Range]	Yes [102dB]	Yes [102dB]	Yes [120dB]	Yes [120dB]	Yes [120dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	30 fps	30 fps	30 fps	30 fps	30 fps
Audio (In / Out / Built-in MIC)	— / — / —	— / — / —	— / — / Yes	— / — / —	— / — / —
External I/O	—	—	—	—	—
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	— / —	— / —	— / —	— / —	— / —
Operating Temperature	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F
Power Source / Consumption	PoE 6.5W	PoE 5.3W	PoE 5.8W	PoE 5.8W	PoE 4.8W
Other	—	—	—	—	—
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS	BRACKETS

BULLET
CAMERAS



COMING SOON



COMING SOON



COMING SOON

MODEL#	WV-X15701-Z3L (Z3LN)	WV-X15700-V2L (V2LN)	WV-X15600-V2L (V2LN)	WV-X15502-Z1L (Z1LN)	WV-X15501-Z3L (Z3LN)
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	8MP(4K)	8MP(4K)	6MP	5MP	5MP
Analytics (Max. # of AI apps installation)	Edge AI (9) / AI relay / On-site learning	Edge AI (9) / AI relay / On-site learning	Edge AI (9) / AI relay / On-site learning	Edge AI (9) / AI relay / On-site learning	Edge AI (9) / AI relay / On-site learning
Sensor	1/2.8 CMOS	1/1.8 CMOS	1/1.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	4.5 to 135 mm, F1.8	4.3 to 8.6 mm, F1.5	4.3 to 8.6 mm, F1.5	4.7 to 47 mm, F1.6	4.5 to 135 mm, F1.8
Optical Zoom	30x, Motorized	2x, Motorized	2x, Motorized	10x, Motorized	30x, Motorized
Horizontal angle of view (16:9)	2.5° to 62°	53° to 104°	53° to 104°	6.1° to 58°	2.3° to 58°
Built-in IR-LED	140 m / 459 ft.	70 m / 230 ft.	70 m / 230 ft.	180 m / 591 ft.	180 m / 591 ft.
Min. Illumination (Color / B&W)	0.13 lx / 0 lx	0.04 lx / 0 lx	0.04 lx / 0 lx	0.04 lx / 0 lx	0.06 lx / 0 lx
WDR [Dynamic Range]	Yes [132dB]	Yes [132dB]	Yes [132dB]	Yes [132dB]	Yes [132dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	60 fps	60 fps	60 fps	60 fps	60 fps
Audio (In / Out / Built-in MIC)	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —
External I/O	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	IP67, IP66 / IK10	IP67, IP66 / IK10	IP67, IP66 / IK10	IP67, IP66 / IK10	IP67, IP66 / IK10
Operating Temperature	-40 °C to +60 °C -40 °F to +140 °F	-40 °C to +55 °C -40 °F to +131 °F	-40 °C to +55 °C -40 °F to +131 °F	-40 °C to +60 °C -40 °F to +140 °F	-40 °C to +60 °C -40 °F to +140 °F
Power Source / Consumption	PoE++ / PoE+ / 12V DC [*2] 32.4W (PoE++)	PoE+ / 12V DC [*2] 14.0W (PoE+)	PoE+ / 12V DC [*2] 14.0W (PoE+)	PoE++ / PoE+ / 12V DC [*2] 32.4W (PoE++)	PoE++ / PoE+ / 12V DC [*2] 32.4W (PoE++)
Other	FIPS 140-2 LV3 [*1], ClearSight (Z3LN)	FIPS 140-2 LV3 [*1], ClearSight (V2LN), Re-paintable	FIPS 140-2 LV3 [*1], ClearSight (V2LN), Re-paintable	FIPS 140-2 LV3 [*1], ClearSight (Z1LN), LPF for LPR	FIPS 140-2 LV3 [*1], ClearSight (Z3LN)
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS	BRACKETS

[*1] FIPS 140-2 level 3-certified secure element is embedded. [*2] Option cable WV-QCA501A is needed.

BULLET CAMERAS



COMING SOON



COMING SOON



COMING SOON



MODEL#	WV-X15501-Z1L (Z1LN)	WV-X15500-V3L (V3LN)	WV-X15302-Z1L (Z1LN)	WV-X15301-Z1L (Z1LN)	WV-X15300-V3L (V3LN)
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	5MP	5MP	2MP	2MP	2MP
Analytics (Max. # of AI apps installation)	Edge AI (9)	Edge AI (9) / AI relay / On-site learning	Edge AI (9)	Edge AI (9)	Edge AI (9) / AI relay / On-site learning
Sensor	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	4.7 to 47 mm, F1.6	2.9 to 9 mm, F1.3	4.7 to 47 mm, F1.6	4.7 to 47 mm, F1.6	2.9 to 9 mm, F1.3
Optical Zoom	10x, Motorized	3.1x, Motorized	10x, Motorized	10x, Motorized	3.1x, Motorized
Horizontal angle of view (16:9)	6.1° to 58°	34° to 106°	6.6° to 62°	6.6° to 62°	37° to 117°
Built-in IR-LED	180 m / 591 ft.	70 m / 230 ft.	250 m / 820 ft.	250 m / 820 ft.	70 m / 230 ft.
Min. Illumination (Color / B&W)	0.04 lx / 0 lx	0.03 lx / 0 lx	0.011 lx / 0 lx	0.011 lx / 0 lx	0.007 lx / 0 lx
WDR [Dynamic Range]	Yes [132dB]	Yes [132dB]	Yes [144dB]	Yes [144dB]	Yes [144dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	60 fps	60 fps	60 fps	60 fps	60 fps
Audio (In / Out / Built-in MIC)	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —
External I/O	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	IP67, IP66 / IK10	IP67, IP66 / IK10	IP67, IP66 / IK10	IP67, IP66 / IK10	IP67, IP66 / IK10
Operating Temperature	-40 °C to +60 °C -40 °F to +140 °F	-40 °C to +55 °C -40 °F to +131 °F	-40 °C to +60 °C -40 °F to +140 °F	-40°C to +60°C -40 °F to +140 °F	-40 °C to +55 °C -40 °F to +140 °F
Power Source / Consumption	PoE++ / PoE+ / 12V DC [*2] 32.4W (PoE++)	PoE+ / 12V DC [*2] 14.0W (PoE+)	PoE++ / PoE+ / 12V DC [*2] 32.4W (PoE++)	PoE++ / PoE+ / 12V DC [*2] 32.4W (PoE++)	PoE+ / 12V DC [*2] 14.0W (PoE+)
Other	FIPS 140-2 LV3 [*1], ClearSight (Z1LN)	FIPS 140-2 LV3 [*1], ClearSight (V3LN), Re-paintable	FIPS 140-2 LV3 [*1], ClearSight (Z1LN), LPF for LPR	FIPS 140-2 LV3 [*1], ClearSight (Z1LN)	FIPS 140-2 LV3 [*1], ClearSight (V3LN), Re-paintable
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS	BRACKETS

BULLET CAMERAS



COMING SOON



COMING SOON



COMING SOON

MODEL#	WV-S15701-Z3L (Z3LN)	WV-S15700-V2L (V2LN) (V2LK)	WV-S15600-V2L (V2LN)	WV-S15501-Z3L (Z3LN)	WV-S15501-Z1L (Z1LN)
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	8MP(4K)	8MP(4K)	6MP	5MP	5MP
Analytics (Max. # of AI apps installation)	Edge AI (3)	Edge AI (3)	Edge AI (3)	Edge AI (3)	Edge AI (3)
Sensor	1/2.8 CMOS	1/1.8 CMOS	1/1.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	4.5 to 135 mm, F1.8	4.3 to 8.6 mm, F1.5	4.3 to 8.6 mm, F1.5	4.5 to 135 mm, F1.8	4.7 to 47 mm, F1.6
Optical Zoom	30x, Motorized	2x, Motorized	2x, Motorized	30x, Motorized	10x, Motorized
Horizontal angle of view (16:9)	2.5° to 62°	53° to 104°	53° to 104°	2.3° to 58°	6.1° to 58°
Built-in IR-LED	140 m / 459 ft.	70 m / 230 ft.	70 m / 230 ft.	180 m / 591 ft.	180 m / 591 ft.
Min. Illumination (Color / B&W)	0.13 lx / 0 lx	0.04 lx / 0 lx	0.04 lx / 0 lx	0.06 lx / 0 lx	0.04 lx / 0 lx
WDR [Dynamic Range]	Yes [132dB]	Yes [132dB]	Yes [132dB]	Yes [132dB]	Yes [132dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	30 fps	30 fps	30 fps	30 fps	30 fps
Audio (In / Out / Built-in MIC)	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —
External I/O	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	IP67, IP66 / IK10	IP66 / IK10	IP66 / IK10	IP67, IP66 / IK10	IP67, IP66 / IK10
Operating Temperature	-40 °C to +60 °C -40 °F to +140 °F	-40 °C to +60 °C -40 °F to +140 °F	-40 °C to +60 °C -40 °F to +140 °F	-40 °C to +60 °C -40 °F to +140 °F	-40 °C to +60 °C -40 °F to +140 °F
Power Source / Consumption	PoE++ / PoE+ / 12V DC [*2] 32.4W (PoE++)	PoE / 12V DC [*2] 11.5W (PoE)	PoE / 12V DC [*2] 11.5W (PoE)	PoE++ / PoE+ / 12V DC [*2] 32.4W (PoE++)	PoE++ / PoE+ / 12V DC [*2] 32.4W (PoE++)
Other	FIPS 140-2 LV3 [*1], ClearSight (Z3LN)	FIPS 140-2 LV3 [*1], ClearSight (V2LN) (V2LK), Re-paintable, Salt resistant (V2LK)	FIPS 140-2 LV3 [*1], ClearSight (V2LN), Re-paintable	FIPS 140-2 LV3 [*1], ClearSight (Z3LN)	FIPS 140-2 LV3 [*1], ClearSight (Z1LN)
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS	BRACKETS

[*1] FIPS 140-2 level 3-certified secure element is embedded. [*2] Option cable WV-QCA501A is needed.

BULLET CAMERAS



COMING SOON

MODEL#	WV-S15500-V3L (V3LN)(V3LN1)(V3LK)	WV-S15500-F6L	WV-S15500-F3L	WV-S15301-Z1L (Z1LN)
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	5MP	5MP	5MP	2MP
Analytics (Max. # of AI apps installation)	Edge AI (3)	Edge AI (3)	Edge AI (3)	Edge AI (3)
Sensor	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS
Focal length / F-number	2.9 to 9 mm, F1.3	6.1 mm, F1.6	3.2 mm, F2.0	4.7 to 47 mm, F1.6
Optical Zoom	3.1x, Motorized	—	—	10x, Motorized
Horizontal angle of view (16:9)	34° to 106°	49°	98°	6.6° to 62°
Built-in IR-LED	55 m / 180 ft.	45 m / 148 ft.	35 m / 115 ft.	250 m / 820 ft.
Min. Illumination (Color / B&W)	0.05 lx / 0 lx	0.08 lx / 0 lx	0.12 lx / 0 lx	0.011 lx / 0 lx
WDR [Dynamic Range]	Yes [132dB]	Yes [132dB]	Yes [132dB]	Yes [144dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	30 fps	30 fps	30 fps	60 fps
Audio (In / Out / Built-in MIC)	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —
External I/O	Yes [*2]	Yes [*2]	Yes [*2]	Yes [*2]
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	IP66 / IK10	IP66 / IK10	IP66 / IK10	IP66 / IK10
Operating Temperature	-40 °C to +60 °C -40°F to +140°F	-40 °C to +60 °C -40°F to +140°F	-40 °C to +60 °C -40°F to +140°F	-40 °C to +60 °C -40 °F to +140 °F
Power Source / Consumption	PoE / 12V DC [*2] 11.5W (PoE)	PoE / 12V DC [*2] 10.6W (PoE)	PoE / 12V DC [*2] 10.6W (PoE)	PoE++ / PoE+ / 12V DC [*2] 32.4W (PoE++)
Other	FIPS 140-2 LV3 [*1], ClearSight (V3LN) (V3LN1) (V3LK), Black (V3LN1) / Re-paintable, Salt resistant (V3LK)	FIPS 140-2 LV3 [*1], Re-paintable	FIPS 140-2 LV3 [*1], Re-paintable	FIPS 140-2 LV3 [*1], ClearSight (Z1LN)
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS

BULLET CAMERAS



MODEL#	WV-S1536LA (LA-B)(LNA)(LNA-B)(LNSA)	WV-S1536LTA (LTNA)	WV-U1542LA	WV-U1532LA
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	2MP	2MP	4MP	2MP
Analytics (Max. # of AI apps installation)	Edge AI (2)	Edge AI (2)	VMD	VMD
Sensor	1/2.8 MOS	1/2.8 MOS	1/2.7 CMOS	1/3 CMOS
Focal length / F-number	2.9 to 9 mm, F1.3	9 to 21 mm, F1.7	2.9 to 7.3 mm, F2.0	2.9 to 7.3 mm, F2.0
Optical Zoom	3.1x, Motorized	2.3x, Motorized	2.5x, Motorized	2.5x, Motorized
Horizontal angle of view (16:9)	37° to 117°	15° to 36°	44° to 103°	43° to 100°
Built-in IR-LED	70 m / 230 ft.	70 m / 230 ft.	20 m / 65 ft.	30 m / 98 ft.
Min. Illumination (Color / B&W)	0.007 lx / 0 lx	0.011 lx / 0 lx	0.3 lx / 0 lx	0.1 lx / 0 lx
WDR [Dynamic Range]	Yes [144dB]	Yes [144dB]	Yes [102dB]	Yes [120dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	60 fps	60 fps	30 fps	30 fps
Audio (In / Out / Built-in MIC)	Yes [*2] / Yes [*2] / —	Yes [*2] / Yes [*2] / —	— / — / —	— / — / —
External I/O	Yes [*2]	Yes [*2]	—	—
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	IP66 / IK10	IP66 / IK10	IP66 / IK10	IP66 / IK10
Operating Temperature	-40 °C to +60 °C -40°F to +140°F	-40 °C to +60 °C -40°F to +140°F	-30 °C to +50 °C -22°F to +122°F	-30 °C to +50 °C -22°F to +122°F
Power Source / Consumption	PoE / 12V DC [*2] 9.1W (PoE)	PoE / 12V DC [*2] 10.6W (PoE)	PoE 7.2W	PoE 6.7W
Other	FIPS 140-2 LV3 [*1], ClearSight (LNA) (LNA-B) (LNSA), Black (LA-B) (LNA-B), Re-paintable, Salt resistant (LNSA)	FIPS 140-2 LV3 [*1], ClearSight (LTNA), Re-paintable	—	—
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS

[*1] FIPS 140-2 level 3-certified secure element is embedded. [*2] Option cable WV-QCA501A is needed.

BOX
CAMERAS



MODEL#	WV-S1136A	WV-U1142A	WV-U11300-V2	WV-U1132A	WV-U1130A
Environmental Type	Indoor	Indoor	Indoor	Indoor	Indoor
Resolution	2MP	4MP	2MP	2MP	2MP
Analytics (Max. # of AI apps installation)	Edge AI (2)	VMD	VMD	VMD	VMD
Sensor	1/2.8 MOS	1/2.7 CMOS	1/2.8 CMOS	1/3 CMOS	1/3 CMOS
Focal length / F-number	CS Mount *Lens is not included	2.9 to 7.3 mm, F2.0	2.9 to 7.3 mm, F2.0	2.9 to 7.3 mm, F2.0	3.2 mm, F2.0
Optical Zoom	—	2.5x, Motorized	2.5x, Motorized	2.5x, Motorized	—
Horizontal angle of view (16:9)	—	44° to 103°	43° to 100°	43° to 100°	100°
Built-in IR-LED	—	—	—	—	—
Min. Illumination (Color / B&W)	0.008 lx / 0.004 lx @F1.2	0.3 lx / 0.12 lx	0.1 lx / 0.04 lx	0.1 lx / 0.04 lx	0.1 lx / 0.04 lx
WDR [Dynamic Range]	Yes [144dB]	Yes [102dB]	Yes [120dB]	Yes [120dB]	Yes [120dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	60 fps	30 fps	30 fps	30 fps	30 fps
Audio (In / Out / Built-in MIC)	Yes / Yes / —	— / — / —	— / — / Yes	— / — / —	— / — / —
External I/O	Yes	—	—	—	—
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	— / —	— / —	— / —	— / —	— / —
Operating Temperature	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F
Power Source / Consumption	PoE / 12V DC 6.3W (PoE)	PoE 4.8W	PoE 4.3W	PoE 4.3W	PoE 3.8W
Other	FIPS 140-2 LV3 [*1]	—	—	—	—
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS	BRACKETS

FISHEYE
CAMERAS



MODEL#	WV-S4576LA WV-S4576LMA	WV-S4556LA WV-S4556LMA	WV-S4176A	WV-S4156A
Environmental Type	Outdoor	Outdoor	Indoor	Indoor
Resolution	12MP	5MP	12MP	5MP
Analytics (Max. # of AI apps installation)	Edge AI (3)	Edge AI (3)	Edge AI (3)	Edge AI (3)
Sensor	1/2 CMOS	1/3 CMOS	1/2 CMOS	1/3 CMOS
Focal length / F-number	1.4 mm, F1.9	0.84 mm, F2.4	1.4 mm, F1.9	0.84 mm, F2.4
Optical Zoom	—	—	—	—
Horizontal angle of view (16:9)	183°	186°	183°	186°
Built-in IR-LED	14 m / 46 ft.	14 m / 46 ft.	—	—
Min. Illumination (Color / B&W)	0.3 lx / 0 lx	0.15 lx / 0 lx	0.3 lx / 0.2 lx	0.15 lx / 0.1 lx
WDR [Dynamic Range]	[84dB]	Yes [120dB]	[84dB]	Yes [120dB]
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	30 fps	30 fps	30 fps	30 fps
Audio (In / Out / Built-in MIC)	Yes / Yes / —	Yes / Yes / —	Yes / Yes / Yes	Yes / Yes / Yes
External I/O	Yes	Yes	Yes	Yes
SD Memory Card Slot	SDXC	SDXC	SDXC	SDXC
Weather / Vandal Resistant	IP66 / IK10, 50J	IP66 / IK10, 50J	— / —	— / —
Operating Temperature	-40 °C to +60 °C -40°F to +140°F	-40 °C to +60 °C -40°F to +140°F	-10 °C to +50 °C +14°F to +122°F	-10 °C to +50 °C +14°F to +122°F
Power Source / Consumption	PoE / 12V DC 12.95W (PoE)	PoE / 12V DC 12.5W (PoE)	PoE / 12V DC 8.6W (PoE)	PoE / 12V DC 6.7W (PoE)
Other	FIPS 140-2 LV3 [*1], Re-paintable, Railway Application/ M12 connector (S4576LMA)	FIPS 140-2 LV3 [*1], Re-paintable, Railway Application/ M12 connector (S4556LMA)	FIPS 140-2 LV3 [*1]	FIPS 140-2 LV3 [*1]
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS

[*1] FIPS 140-2 level 3-certified secure element is embedded.

OUTDOOR
COMPACT
CAMERAS



MODEL#	WV-X35402-F2L (F2LM) WV-S35402-F2L (F2LG)(F2L1)	WV-X35302-F2L (F2LM) WV-S35302-F2L (F2LG)(F2L1)	WV-U35401-F2L (F2LG)	WV-U35301-F2L (F2LG)	WV-SBV131M
Environmental Type	Outdoor	Outdoor	Outdoor	Outdoor	Outdoor
Resolution	4MP	2MP	4MP	2MP	2MP
Analytics (Max. # of AI apps installation)	Edge AI (1)	Edge AI (2)	VMD	VMD	VMD
Sensor	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/3 CMOS
Focal Length / F-number	2.4mm, F2.1	2.4mm, F2.1	2.4mm, F2.1	2.4mm, F2.1	1.95 mm, F2.2
Optical Zoom	—	—	—	—	—
Horizontal Angle of View (16:9)	121°	132°	128°	123°	109°
Built-in IR-LED	14 m / 46 ft. 10 m / 33 ft. (F2LG)	21 m / 69 ft. 15 m / 49 ft. (F2LG)	14 m / 46 ft. 10 m / 33 ft. (F2LG)	21 m / 69 ft. 15 m / 49 ft. (F2LG)	—
Min. Illumination (Color / B&W)	0.07 lx / 0 lx	0.02 lx / 0 lx	0.24 lx / 0 lx	0.08 lx / 0 lx	0.1 lx / 0.06 lx
WDR [Dynamic Range]	Yes [132dB]	Yes [144dB]	Yes [102dB]	Yes [120dB]	Yes
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.264 Smart Coding
Max. fps @Max. Resolution	30 fps	60 fps	30 fps	30 fps	30 fps
Audio (In / Out / Built-in MIC)	— / — / Yes	— / — / Yes	— / — / Yes	— / — / Yes	— / — / —
External I/O	—	—	—	—	—
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC	SDXC
Weather / Vandal Resistant	IP66 / IK10	IP66 / IK10	IP66 / IK10	IP66 / IK10	IP6K9K, IP66 / IK10
Operating Temperature	-40 °C to +60 °C (X-series) -40°F to +140°F (X-series) -30 °C to +50 °C (S-series) -22°F to +122°F (S-series)	-40 °C to +60 °C (X-series) -40°F to +140°F (X-series) -30 °C to +50 °C (S-series) -22°F to +122°F (S-series)	-30 °C to +50 °C -22°F to +122°F	-30 °C to +50 °C -22°F to +122°F	-40 °C to +60 °C -40°F to +140°F
Power Source / Consumption	PoE 8.6W (PoE)	PoE 8.6W (PoE)	PoE 8.6W (PoE)	PoE 8.6W (PoE)	PoE 3.8W
Other	FIPS 140-2 LV3 [*1], Railway standards (X-series), M12 connector (F2LM), Smoke dome (F2LG), Black (F2L1)	FIPS 140-2 LV3 [*1], Railway standards (X-series), M12 connector (F2LM), Smoke dome (F2LG), Black (F2L1)	Smoke dome (F2LG)	Smoke dome (F2LG)	MIL-STD-810G, EN50155-T3, EN50121, EN45545, EN50498, ECE-R10, M12 connector
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS	BRACKETS

INDOOR
COMPACT
CAMERAS



MODEL#	WV-S32402-F2L (F2LG) (F2L1)	WV-S32302-F2L (F2LG) (F2L1)	WV-U31401-F2L (F2LG)	WV-U31301-F2L (F2LG)	WV-S71300A-F3
Environmental Type	Indoor Vandal	Indoor Vandal	Indoor	Indoor	Indoor
Resolution	4MP	2MP	4MP	2MP	2MP
Analytics (Max. # of AI apps installation)	Edge AI (1)	Edge AI (2)	VMD	VMD	Edge AI (3)
Sensor	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.8 CMOS	1/2.8 MOS
Focal length / F-number	2.4mm, F2.1	2.4mm, F2.1	2.4mm, F2.1	2.4mm, F2.1	3.2mm, F2.0
Optical Zoom	—	—	—	—	—
Horizontal angle of view (16:9)	121°	132°	128°	123°	81.1°
Built-in IR-LED	14 m / 46 ft. 10 m / 33 ft. (F2LG)	21 m / 69 ft. 15 m / 49 ft. (F2LG)	14 m / 46 ft. 10 m / 33 ft. (F2LG)	21 m / 69 ft. 15 m / 49 ft. (F2LG)	—
Min. Illumination (Color / B&W)	0.07 lx / 0 lx	0.02 lx / 0 lx	0.24 lx / 0 lx	0.08 lx / 0 lx	0.21 lx / 0.2 lx
WDR [Dynamic Range]	Yes [132dB]	Yes [144dB]	Yes [102dB]	Yes [120dB]	—
Video Codec	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding	H.265 Smart Coding
Max. fps @Max. Resolution	30 fps	60 fps	30 fps	30 fps	30 fps
Audio (In / Out / Built-in MIC)	— / — / Yes	— / — / Yes	— / — / Yes	— / — / Yes	— / — / Yes
External I/O	—	—	—	—	—
SD Memory Card Slot	microSDXC	microSDXC	microSDXC	microSDXC	microSDXC
Weather / Vandal Resistant	— / IK10	— / IK10	— / —	— / —	IP44 / —
Operating Temperature	0 °C to +40 °C +32°F to +104°F	0 °C to +40 °C +32°F to +104°F	0 °C to +40 °C +32°F to +104°F	0 °C to +40 °C +32°F to +104°F	-10 °C to +40 °C +14°F to +104°F
Power Source / Consumption	PoE 8.6W (PoE)	PoE 8.6W (PoE)	PoE 8.6W (PoE)	PoE 8.6W (PoE)	PoE / USB Type-C 8.2W (PoE)
Other	FIPS 140-2 LV3 [*1], Smoke dome (F2LG), Black (F2L1)	FIPS 140-2 LV3 [*1], Smoke dome (F2LG), Black (F2L1)	Smoke dome (F2LG)	Smoke dome (F2LG)	FIPS 140-2 LV3 [*1], USB I/F for setting thru Wi-Fi
Bracket Chart	BRACKETS	BRACKETS	BRACKETS	BRACKETS	BRACKETS

[*1] FIPS 140-2 level 3-certified secure element is embedded.

NVR WJ-NX310/NX410/NX510 Series

NX Series Features

- Secure high-bandwidth recording
- High reliability and redundancy
- Scalable storage
- High security
 - GlobalSign® certificates pre-installed
 - FIPS 140-2 LV3 [*1]
- Onvif/RTSP supported
- Remote Monitoring

[*1] FIPS 140-2 level 3-certified secure element is embedded



NVRs

MODEL#	WJ-NX310	WJ-NX410	WJ-NX510	WJ-HXE410
Type	NETWORK VIDEO RECORDERS			HDD Extension Unit
Video Compression	H.265 / H.264 / JPEG			
Camera Channel	Default / Max	16 ch / 32 ch	32 ch / 64 ch	64 ch / 128 ch
PoE port	—			
Throughput	Recording / Output	256 Mbps / 256 Mbps	384 Mbps / 256 Mbps	—
Max HDD	4 HDDs	9 HDDs (Main Unit) 54 HDDs (with 5 x WJ-HXE410)	9 HDDs	—
Max HDD capacity for each SATA	Up to 18TB			
RAID	RAID 1	RAID 1, 5, 6		
Monitor Output	2 x HDMI (4K)			—
Alarm Port	9 inputs / 1 output	32 inputs / 4 outputs	—	—
Simultaneous User Access	Max 16 users			—
Network Interface	2 x 1000BASE-T	2 x 1000BASE-T, 1 x 100BASE-TX (for maintenance)	—	—
Operating Temperature	0°C to +45°C / +32°F to +113°F			
Dimensions (inch)	(W)420 x (D)370 x (H)88(mm) (W)16-17/32 x (D)14-9/16 x (H)3-15/32(inches)	(W)430 x (D)413 x (H)132(mm) (W)16-15/16 x (D)16-1/4 x (H)5-3/16(inches)	(W)430 x (D)416 x (H)132(mm) (W)16-15/16 x (D)16-3/8 x (H)5-3/16(inches)	—
Weight	7 kg /15.4 lbs. (no HDD)	11.5 kg / 25.4 lbs. (no HDD)	11.0 kg / 24.3 lbs. (no HDD)	—
Standard Accessory	Rack mount			
Model Number	WJ-NX310/8000T8 8TB Model (1 x 8TB HDD) WJ-NX310/18000T18 18TB Model (1 x 18TB HDD) WJ-NX310/32000T8 32TB Model (4 x 8TB HDD) WJ-NX310/72000T18 72TB Model (4 x 18TB HDD)	WJ-NX410/8000T8 8TB Model (1 x 8TB HDD) WJ-NX410/18000T18 18TB Model (1 x 18TB HDD) WJ-NX410/72000T8 72TB Model (9 x 8TB HDD) WJ-NX410/162T18 162TB Model (9 x 18TB HDD)	WJ-NX510/8000T8 8TB Model (1 x 8TB HDD) WJ-NX510/18000T18 18TB Model (1 x 18TB HDD) WJ-NX510/72000T8 72TB Model (9 x 8TB HDD) WJ-NX510/162T18 162TB Model (9 x 18TB HDD)	WJ-HXE410/8000T8 8TB Model (1 x 8TB HDD) WJ-HXE410/18000T18 18TB Model (1 x 18TB HDD) WJ-HXE410/72000T8 72TB Model (9 x 8TB HDD) WJ-HXE410/162T18 162TB Model (9 x 18TB HDD)

OPTIONAL ACCESSORIES				
	FOR WJ-NX310	FOR WJ-NX410	FOR WJ-NX510	FOR WJ-HXE410
HDD				
	CANISTER-NX3/8TB (8TB)	CANISTER-NX4/8TB (8TB)		
	CANISTER-NX3/18TB (18TB)	CANISTER-NX4/18TB (18TB)		
HDD Extension Unit	—	WJ-HXE410		
Additional License	Camera CH Kit	WJ-NXE32W (8 camera license)	WJ-NXE42W (32 camera license)	WJ-NXE52W (32 camera license)
		WJ-NXE33W (16 camera license)		WJ-NXE53W (64 camera license)
	Data Encryption Kit	WJ-NXS01W (1 camera) / WJ-NXS04W (4 cameras) / WJ-NXS16W (16 cameras) / WJ-NXS32W (32 cameras)		

NVR with a build-in PoE+ switch WJ-NU101 / 201 / 300 / 301 Series

NU Series Features

- NVR with a build-in PoE+ switch
- Easy installation
- Scalable Storage
- Perfectly adapted to i-PRO AI products
- High security
 - GlobalSign® certificates pre-installed
 - FIPS 140-2 LV3 [*1]
- Connectivity
 - RTSP supported
- Remote monitoring

[*1] FIPS 140-2 level 3-certified secure element is embedded



NVR with a build-in PoE+ switch

MODEL#	WJ-NU101	WJ-NU201	WJ-NU300	WJ-NU301
	NVR WITH A BUILD-IN POE+ SWITCH			
Video Compression	H.265 / H.264 / JPEG			
Max Camera Channel	4 ch	8 ch	16 ch	
Video Throughput	Recording / Output	48Mbps/48Mbps	64Mbps/64Mbps	128Mbps/128Mbps
HDD slot	1 HDD (Main Unit)			2 HDDs (Main Unit)
Max HDD capacity for each SATA	Up to 20 TB			
Network Interface	4x 10BASE-T 100BASE-TX (RJ45, PoE+)	1 x 10BASE-T 100BASE-TX 1000BASE-T (RJ45)	8x 10BASE-T 100BASE-TX (RJ45, PoE+)	1 x 10BASE-T 100BASE-TX 1000BASE-T (RJ45)
PoE budget	4 port Total Max 50W Each port Max:30W	8 port Total Max 110W Each port Max:30W	16 port Total Max 233W Each port Max:30W	—
RAID	—			RAID1
Monitor Output	2 x HDMI (1x 4K, 1x Full HD)			
Alarm port	In:4 / out:1 (Additional General purpose I/O :2)			
Simultaneous User Access	Max 16 users			
Operating temperature	0°C to +45°C / +32°F to +113°F			
Dimensions (inch)	(W)340 x (D)230 x (H)44(mm) (W)13-3/8 x (D)9-1/16 x (H)1-23/32(inches)			(W)420 x (D)300 x (H)88(mm) (W)16-17/32 x (D)11-13/16 x (H)3-15/32(inches)
Weight	2.1 kg / 4.6 lbs			4.7 kg / 10.4 lbs
	RACK MOUNT COMPATIBILITY			
WV-QRM001	Rack mount bracket for vertical installation			—
WV-QRM101	Rack mount bracket			—
WV-QRM201	Rack mount bracket for wall mounting			Rack mount bracket

Rack mount bracket

OPTIONAL ACCESSORIES				
Usage	Vertical installation	Rack mount Bracket	Wall mounting	Rack mount Bracket
MODEL#	WV-QRM001	WV-QRM101	WV-QRM201	
Image				

Management Software

i-PRO Management Software

WV-ASM300W

Extension Software

WV-ASE202W / WV-ASE203W / WV-ASE205W

Easy setting: New WV-ASM300W software enable a whole setting from camera configuration to recorder configuration.

- Up to 100 recorders, 64 encoders and 256 directly connected cameras can be registered. Up to 6,400 cameras registered in the recorders and 256 cameras registered in the encoders are automatically registered in the WV-ASM300W (the number of the cameras depends on the recorder and encoder).
- Encryption of SSL and data encryption support latest "AES-256bit key" strong encryption.
- MP4 data direct download from WJ-NX310, NX410, NX510, NU101, NU201, NU300, NU301.
- When used with WJ-NX310, NX410, NX510, NU101, NU201, NU300, NU301, VMD, thumbnail search can be operated.
- Selecting the camera icon in map window, a still image of the camera is overlaid.
- Live window, Map window in addition to the Operation window (3 monitors).
- Control using the System Controller WV-CU980
https://i-pro.com/products_and_solutions/en/surveillance/products/wv-cu980
- 3D Dewarp: virtual PTZ operations for better operability and monitoring experience.

*To use the multi-monitor function, it is necessary to install an additional video card on the PC in use.



*monitor displays are optional.

Optional software

WV-ASE202W

- Expand the maximum numbers of screens to 64.
- Up to 4 live windows.
- Multi-monitor function using up to 6 PC monitors.
- To display the operation window, the map window and the 4 map windows simultaneously.

WV-ASE203W

- Expand the maximum numbers of registered recorders, encoders and cameras to 100, 64 and 256 respectively.
- Up to 4 licenses for the WV-ASE203W can be added.

WV-ASE205W

- Visibility Enhancement Function.

Spatial Tonal Correction

Snowfall and Rainfall Noise Reduction

Multi-frame Synthesis Noise Reduction

i-PRO Mobile APP

Applications for Smartphone/Tablet PC




Overview

i-PRO Mobile APP is a smartphone application that can view the images of the following i-PRO devices.

- Network cameras
- Network interface units
- Digital disk recorders
- Network disk recorders

Functions

- Check live video
- Control live video
- Play recorded video
- Download playback video
- Check statistics in a graph
- Alarm notification



For Android



For iOS



Accessories

i-PRO SD MEMORY CARDS



MODEL#	WV-SDA032G	WV-SDA064G	WV-SDA128G	WV-SDA256G	WV-SDA512G
Type	SDHC	SDXC	SDXC	SDXC	SDXC
Storage	32 GB	64 GB	128 GB	256 GB	512 GB

i-PRO MICRO SD MEMORY CARDS



MODEL#	WV-SDB032G	WV-SDB064G	WV-SDB128G	WV-SDB256G
Type	microSDHC	microSDXC	microSDXC	microSDXC
Storage	32 GB	64 GB	128 GB	256 GB



MICROPHONE

MODEL#	WV-PM500
Directionality	Non-directional
Power	Plug-in power type, 1.5 VDC to 5 VDC, Max. current: 300 uA
Terminal / Cable	3.5 mm stereo mini plug (L ch monaural) Cable length: 2.6 m / 8.53 ft.
Operating Temperature	-20 °C to +60 °C / -4 °F to +140 °F
Dust and Water Resistant	IP65



POE INJECTOR

MODEL#	WJ-PU201/G	WJ-PU201F/G
Power Input	100 to 240V AC	100 to 240V AC
Max. Power output	60W @ -10 °C to +40 °C, 60W @ +14°F to +104 °F 30W @ -10 °C to +50 °C, 30W @ +14°F to +122 °F	60W @ -10 °C to +40 °C, 60W @ +14°F to +104 °F 30W @ -10 °C to +50 °C, 30W @ +14°F to +122 °F
Network Interface	10BASE-T/100BASE-TX/1000BASE-T, RJ45 connector (x2)	10BASE-T/100BASE-TX/1000BASE-T, RJ45 connector (x2) Standard SFP module port (LC type) (x1)
IEEE Standards	IEEE802.3bt/at/af	IEEE802.3bt/at/af
Dimensions	(W) 65 mm x (D) 163 mm x (H) 36 mm (W) 2-9/16 x (D) 6-13/32 (inches) x (H) 1-13/32 (inches)	(W) 80 mm x (D) 184 mm x (H) 50 mm (W) 3-5/32 x (D) 7-1/4 x (H) 1-31/32 (inches)

COAXIAL-LAN CONVERTER



MODEL#	WJ-PC200	WJ-PR204	WJ-PR201
Device Type	Camera Side Unit	4CH Receiver	1CH Receiver
Max. Distance w/ AC adaptor	PoE cam non - PoE cam	— 500 m (1,640 ft)	500 m (1,640 ft) 2.0 km (6,561 ft)
Optional Rack Mount	—	BY-HCA10A	



SYSTEM CONTROLLER


MODEL#	WV-CU980
Specifications	Integrated control for Camera, Recorder and GUI: - 3D Joystick for Pan/Tilt/Zoom control - Work with WV-ASM300, Video Insight VIM+ version 7.6 or later * WV-ASM200, WV-ASC970 is not supported

i-PRO Active Guard

Immediate response to or prevention of incidents


- Detect various events such as intruder, on-site learning object, scene change, occupancy, gunshot sound, and watchlist alarm for specific faces, people, vehicle and license plate group. Rule-based action on VMS enables automation of system behavior when an event occurs.
- A mobile application* frees you from work in a monitoring room. Also, by linking the PC software and mobile application, the necessary information can be transmitted from a person in the monitoring room to the security guards outside.

*Video Insight only.



Significant reduction in post investigation time

- Searching by face, license plate, and characteristics of people and vehicles enables fast searching in a matter of seconds, not hours.
- This advantage is maximized by many supported attributes with high precision based on i-PRO deep learning technology and by the high image quality of the i-PRO camera.




Customizable dashboard display for business intelligence

- The dashboard on the web browser shows people counting, license plate counting, face and gender statistics, and people and vehicle attribute statistics. This can be utilized for business intelligence.
- Users can customize the content, size, location, data display period, etc. shown according to their needs.



Flexible system architecture

- Fully integrated into devices from Genetec and Milestone as well as Video Insight.
- No need for expensive analysis server thanks to edge analytics.
- By installing and using the required AI Edge Applications for each camera, you can use the performance of AI without waste.



Edge AI Analytics

GO BEYOND TRADITIONAL ANALYTICS WITH INTELLIGENT SOLUTIONS FROM i-PRO

In today's environment, more users are looking to actively manage large surveillance systems. As these systems become more complex, i-PRO's intelligent analytics can help users by reducing the learning curve and system resources required to operate them. From improving the accuracy of alarms and notifications to reducing the overall system bandwidth and storage requirements, i-PRO Intelligent analytics has you covered.

- Change your surveillance system from reactive to proactive and anticipate situations before they occur.
- i-PRO surveillance users can gain added sight awareness with intelligent analytics via scene analysis.
- Optimized feature solutions for schools, municipalities, and commercial facilities.
- i-PRO analytics may be deployed either at the edge or server level providing a flexible deployment.

ANALYTICS AT THE EDGE




AI-VMD/AI Counting

AI-VMD can identify between objects. The cameras actively read the scene and uniquely differentiate between people, vehicles and two-wheeled vehicles. Additionally, AI-VMD offers users intelligent functionality such as line-cross detection/counting, loitering detection and directional detection.



AI On-site Learning

AI On-site Learning allows to enhance AI-VMD by adding target object and improving accuracy. You can add customized objects to detect using on-site camera footage through simple learning process. In addition, it contributes to reduce missed/false alarms by training based on the past footage.



AI People/Vehicle/Face Detection

These analytics allow you to detect people, vehicles, faces, and send the metadata and best images to the server. They are compatible with i-PRO Active Guard, a search function that quickly finds people or vehicles through the video management software, Video Insight, Genetec, Milestone, Luxriot etc.



AI Scene Change Detection

Scene Change Detection is the first AI-based analytic application that provides easy on-site learning of a scene. When anomalies occur within the camera's field of view, an alert can be sent to security and operations teams. It's particularly good at an object left behind or illegal parking scenarios.



AI Sound Classification

AI Sound Classification allows you to detect suspicious sounds, such as gunshots, screaming, vehicle horns or glass breaking.



AI Privacy Guard

When deployed on i-PRO AI engine cameras, AI Privacy Guard protects the privacy of individuals within the scene by applying a mosaic over their face in real time.



AI Occupancy Detection

When deployed on an i-PRO AI engine camera, AI Occupancy Detection will be able to detect the crowd congestion and send the pop-up alarm notification. Information of the number of people in the area can be output externally via HTTP or MQTT.



AI Processing Relay

AI processing relay enables to turn "non-AI camera" into "AI camera" without any re-installation costs. It receives MJPEG data from non-AI cameras, performs AI processing with AI extension software, and performs alarm reception and image search with i-PRO Active Guard.



System Design Tool

The System Design Tool is a great tool that can be used on the web anytime, anywhere, greatly reducing the work required for system design.

Features and Benefits

- Interactive:
When the camera setting conditions are changed, the perception and size of the subject can be immediately simulated.
- Optimization:
The ideal camera placement and number can be calculated while confirming the overlap in the recording range between cameras.
- Accessible:
Data saved as a project can be accessed from the web at any time.
- Utilization:
Saved device lists and results of storage calculation can be exported in CSV format and utilized for proposal data.



Recorder Calculation

It is possible to estimate the number of recorders and necessary networks that can be used according to the number of cameras, network bandwidth, and number of recording days.

*** Select the target recorder or VMS.**

WV-NX400K WV-NX300K WV-NX200EP WV-NX100 VMS

*** To set [Recording Days/Recording Group: 02], set the target camera to [02] in [Recording Group] of [Extra function].**

Estimate condition

Number of units	HDD capacity	Recording days (Recording group: 01)	HDMI output
Automatic	2TB	150 days	Yes

*** Enter [Recording condition], the necessary device configuration is displayed in [Result].**

*** Select [HDMI output: On], the number of cameras will be limited to 64 standard streams.**

Result

Bandwidth	DATA SIZE			
12.25 Mbps	21.97 TB			
Model	MAIN	EXT	HDD (MAIN / EXT)	Maximum recordable days (Same HDD / Same Unit / Max Config)
WV-NX400K	1	WV-NX400	1	Group 01 9 2
				Group 02 -- --
				Total 11

Camera Kits

Stream numbers	Secure Communication Kits
WV-NX400K	WV-NX320W WV-NX160W
WV-NX400W	WV-NX320W WV-NX160W

System design calculators

Configuration of the recorder and i-PRO Active Guard software can be done with simple operations such as camera selection. Advanced knowledge and skills are not required.

Security Recorder Calculator

i-PRO Active Guard Calculator (for Video Image)

i-PRO Configuration Tool (iCT)


i-PRO Configuration Tool is designed to efficiently configure the settings and maintenance of up to 1,024 i-PRO devices (network cameras, disk recorders, etc.) through a personal computer via a network.

Features and Benefits

- Camera batch settings for up to 1,024 multiple cameras
- Camera advanced settings with image stream viewing screen
- AI extension software batch installation and advanced settings
- Generation of devices settings report with camera view images
- Collective maintenance of devices, including automatic firmware updates

Related products of i-PRO Configuration Tool

- i-PRO Settings Plug-in for Genetec / for Milestone XProtect
- i-PRO Configuration Tool for Tablet (Android/iOS)



Network Camera Model Number Format

Network Camera Model Number Format - 1

W	V	-	S	2	5	3	6	L	T	A
Series								Other Features & Minor changes		
X : eXtraordinary	9 : -		9 : -		9 : -		0 - 9		A-D : Minor Change	
S : Standard	8 : Multi-Sensor		8 : -		8 : -				L : LED	
U : Utility	7 : -		7 : -		7 : 4K				N : ClearSight	
	6 : PTZ (Dome)		6 : -		6 : -				M : M12	
	5 : -		5 : Outdoor Vandal		5 : 5MP				T : Long focal lens	
	4 : 360 deg.		4 : -		4 : 4MP				S : Salt resistant	
	3 : Compact Dome		3 : -		3 : 2MP					
	2 : Dome		2 : Indoor Vandal		2 : -					
	1 : Box		1 : Indoor Normal		1 : 1MP					
	0 : -		0 : -		0 : -					

Network Camera Model Number Format - 2

W	V	-	S	2	5	7	0	0	-	V	2	L	N		
Series										Lens1					
X : eXtraordinary	8 : Multi-Sensor		7 : Outdoor Vandal		7 : 4K		00 - 99	None		F : Fixed lens	None : No lens	L : IR-LED		None : White	
S : Standard	7 : Mini		+ Salt resistance		6 : 6MP			A, B, C		V : Vari-focal	Y, 1 to 9 :	M : M12 connector		1, -1 : Black	
U : Utility	6 : PTZ		6 : Outdoor Vandal		5 : 5MP					T : Long focal	See below	G : Smoke dome		2, -2 : Silver	
	4 : 360-deg		5 : Outdoor Vandal		4 : 4MP					Z : Zoom lens		N : ClearSight		3, -3 : Gray	
	3 : Compact Dome		4 : Outdoor Normal		3 : 2MP					U : No Lens		S : Salt resistant		4, -4 : Brown	
	2 : Dome		2 : Indoor Vandal		1 : 1MP							K : ClearSight & Salt resistant			
	1 : Box		1 : Indoor Normal												

Lens2					
	Y	1	2	3	4
Lens1	F	-	1 - 1.9 mm	2 - 2.9 mm	3 - 3.9 mm
	V, T	-	1x - 1.9x	2x - 2.9x	3x - 3.9x
	Z	< 10x	10x - 19.9x	20x - 29.9x	30x - 39.9x

Accessory Model number structure

W	V	-	Q	S	R	5	0	3	F		-	W
			Product Type			Serial			Option	Version	Color	
			EM : Embedded CL : Ceiling WL : Wall PL : Pole CN : Corner SR : Shroud JB : Junction Box, Base cover	AT : Attachment CA : Cable LR : Light Rail CD : Ceiling Dome WD : Wall+Dome cover ED : Embedded+Dome cover DC : Dome cover				M : Male screw (ISO) M1 : Male screw (ANSI) F : Female screw (ISO) F1 : Female screw (ANSI) C : Clear Dome G : Smoke Dome S : Salt resistant N : ClearSight	None, A, B	G : Gray S : Silver B : Black W : i-PRO white, White		


MULTI-DIRECTIONAL
+ PTZ CAMERAS



OUTDOOR

WV-X86531-Z2	White
WV-X86531-Z2-1	Black
WV-X86530-Z2	White
WV-X86530-Z2-1	Black

ACCESSORIES		
PICTURE	SKU DESCRIPTION	ALL
	WV-QDC502G Smoke Dome	✓
	WV-QDC502C Clear Dome	✓
	WV-QCA501A Multi Cable (Ext I/O, Audio, DC)	✓
	WJ-PU201/G PoE++ injector	✓
	WJ-PU201F/G PoE++ injector	✓
	WV-PM500 Microphone Unit	✓



*Other mounts to install with locally procured pipes/brackets are also available:
WV-QSR508F-W/WV-QSR508F-B (ISO Female), WV-QSR508M-W/WV-QSR508M-B (ISO Male),
WV-QSR508F1-W/WV-QSR508F1-B (ANSI Female), WV-QSR508M1-W/WV-QSR508M1-B (ISO Male)


MULTI-SENSOR
CAMERAS



OUTDOOR

WV-S8574L, LG	White
WV-S8573L, LG	White
WV-S8564L, LG	White
WV-S8563L, LG	White
WV-S8544L, LG	White
WV-S8543L, LG	White
WV-S8544, G	White
WV-S8543, G	White

ACCESSORIES		
PICTURE	SKU DESCRIPTION	ALL
	WV-QDC501G Smoke Dome	✓
	WV-QDC501C Clear Dome	✓
	WV-QCA501A Multi Cable (Ext I/O, Audio, DC)	✓



*Other mounts to install with locally procured pipes/brackets are also available:
WV-QSR503F-W (ISO Female), WV-QSR503M-W (ISO Male),
WV-QSR503F1-W (ANSI Female), WV-QSR503M1-W (ISO Male)


DUAL-SENSOR
CAMERAS



OUTDOOR

WV-S85702-F3L	White
WV-S85702-F3L1	Black
WV-S85402-V2L	White
WV-S85402-V2L1	Black
WV-U85402-V2L	White
WV-U85402-V2L1	Black

ACCESSORIES		
PICTURE	SKU DESCRIPTION	ALL
	WV-CW75 Smoke Dome	✓
	WV-QDC504C Clear Dome	✓
	WV-CW75N Smoke Dome with ClearSight Coating	✓
	WV-CW7CN Clear Dome with ClearSight Coating	✓
	WV-QCA501A Multi Cable (Ext I/O, Audio, DC)	✓



*Other mounts to install with locally procured pipes/brackets are also available:
WV-QSR507F-W/WV-QSR507F-B (ISO Female), WV-QSR507M-W/WV-QSR507M-B (ISO Male),
WV-QSR507F1-W/WV-QSR507F1-B (ANSI Female), WV-QSR507M1-W/WV-QSR507M1-B (ISO Male)

OUTDOOR
PTZ CAMERAS



SALT RESISTANT

WV-X67711-Z3L3	Gray
WV-X67710-Z3-3, Z3L3	Gray
WV-X67710-Z3-1, Z3L1	Black
WV-X67701-Z3L3	Gray
WV-X67700-Z3-3, Z3L3	Gray
WV-X67311-Z4L3	Gray
WV-X67310-Z4-3, Z4L3	Gray
WV-X67310-Z4-1, Z4L1	Black
WV-X67301-Z4L3	Gray
WV-X67300-Z4-3, Z4L3	Gray

ACCESSORIES		
PICTURE	SKU DESCRIPTION	ALL
	WV-QCA502 Multi cable (Ext I/O, Audio, Relay)	✓
	WJ-PU201/G PoE++ injector	✓
	WJ-PU201F/G PoE++ injector	✓



OUTDOOR
PTZ CAMERAS



OUTDOOR

WV-S66700-Z3, Z3L	White
WV-S66700-Z3N, Z3LN	White
WV-S66600-Z3, Z3L	White
WV-S66600-Z3N, Z3LN	White
WV-S66300-Z4, Z4L	White
WV-S66300-Z4N, Z4LN	White
WV-S66300-Z3, Z3L	White
WV-S66300-Z3N, Z3LN	White

SALT RESISTANT

WV-X66700-Z3S, Z3LS	White
WV-X66700-Z3K, Z3LK	White
WV-X66600-Z3S, Z3LS	White
WV-X66600-Z3K, Z3LK	White
WV-X66300-Z4S, Z4LS	White
WV-X66300-Z4K, Z4LK	White
WV-X66300-Z3S, Z3LS	White
WV-X66300-Z3K, Z3LK	White

ACCESSORIES

PICTURE	SKU DESCRIPTION	ALL
	WV-QDC508G Smoke Dome	✓
	WV-QDC508CN Clear Dome with ClearSight Coating	✓
	WV-QDC508C Clear Dome	✓
	WV-QCA501A Multi Cable (Ext I/O, Audio, DC)	✓
	WJ-PU201/G PoE++ injector	✓
	WJ-PU201F/G PoE++ injector	✓
	WV-PM500 Microphone Unit	✓

*Other mounts to install with locally procured pipes/brackets are also available:
WV-QSR506F-W (ISO Female), WV-QSR506M-W (ISO Male),
WV-QSR506F1-W (ANSI Female), WV-QSR506M1-W (ISO Male)

WALL/ POLE/ CORNER		WV-QWL502-W	FOR POLE Mount QWL502 directly	FOR CORNER WV-QCN500-W
		WV-QSR506-W* (4-screw)	WV-QWL501-W	FOR POLE WV-QPL500-W FOR CORNER WV-QCN500-W
HANGING		WV-QSR506-W* (4-screw)	WV-QCL501-W	
CEILING		WV-QJB505-W	WV-Q105A (Indoor only. If needed.)	
RECESSED		WV-QEM505-W (Indoor only)		
WALL		WV-QSR506S-W (4-screw) (Salt resistant)	WV-QWL501S-W (Salt resistant)	FOR POLE WV-QPL500S-W (Salt resistant) FOR CORNER WV-QCN500S-W (Salt resistant)
		WV-QSR506S-W (4-screw) (Salt resistant)	WV-QCL501S-W (Salt resistant)	

OUTDOOR
PTZ CAMERAS



OUTDOOR

WV-X6533LN, WV-S6532LN	Silver
------------------------	--------

SALT RESISTANT

WV-X6533LNS, WV-S6532LNS	Silver
--------------------------	--------

ACCESSORIES

PICTURE	SKU DESCRIPTION	ALL
	WJ-PU201/G PoE++ injector	✓
	WJ-PU201F/G PoE++ injector	✓

OUTDOOR
PTZ CAMERAS



OUTDOOR

WV-S65340-Z4, Z4N, Z4G WV-S65340-Z4N1	White Black
WV-S65340-Z2, Z2N, Z2G WV-S65340-Z2N1	White Black

SALT RESISTANT

WV-S65340-Z4K	White
WV-S65340-Z2K	White

ACCESSORIES

PICTURE	SKU DESCRIPTION	ALL
	WV-QDC503G Smoke Dome	✓
	WV-QDC503C Clear Dome	✓
	WV-QDC503CN Clear Dome with ClearSight coating	✓
	WJ-PU201/G PoE++ injector	✓
	WJ-PU201F/G PoE++ injector	✓
	WV-PM500 Microphone Unit	✓

WALL/ POLE/ CORNER		WV-Q122A Silver	FOR POLE WV-Q188 Silver FOR CORNER WV-Q189 Silver
		WV-QWL504-B	FOR POLE Mount QWL504 directly FOR CORNER WV-Q189 Silver
HANGING		WV-Q121B Silver	
CEILING		WV-QCL500-S Silver	
WALL/ POLE/ CORNER		WV-Q122AS Silver (Salt resistant)	FOR POLE WV-QPL500S-W (Salt resistant) FOR CORNER WV-QCN500S-W (Salt resistant)

WALL/ POLE/ CORNER		WV-QSR504-W* WV-QSR504-B (4-screw)	WV-QWL501-W WV-QWL501-B	FOR POLE WV-QPL500-W WV-QPL500-B FOR CORNER WV-QCN500-W WV-QCN500-B
		WV-QWL504-W WV-QWL504-B		FOR POLE Mount QWL504 directly FOR CORNER WV-QCN500-W WV-QCN500-B
HANGING		WV-QSR504-W* WV-QSR504-B (4-screw)	WV-QCL501-W WV-QCL501-B	
CEILING		WV-QCL500-W		
WALL/ POLE/ CORNER		WV-QSR504S-W (4-screw) (Salt resistant)	WV-QWL501S-W (Salt resistant)	FOR POLE WV-QPL500S-W (Salt resistant) FOR CORNER WV-QCN500S-W (Salt resistant)
		WV-QWL504S-W (Salt resistant)		FOR POLE Mount QWL504 directly FOR CORNER WV-QCN500S-W (Salt resistant)
HANGING		WV-QSR504S-W (4-screw) (Salt resistant)	WV-QCL501S-W (Salt resistant)	

*Other mounts to install with locally procured pipes/brackets are also available:
WV-QSR504F-W/WV-QSR504F-B (ISO Female), WV-QSR504M-W/WV-QSR504M-B (ISO Male),
WV-QSR504F1-W/WV-QSR504F1-B (ANSI Female), WV-QSR504M1-W/WV-QSR504M1-B (ISO Male)

OUTDOOR PTZ CAMERAS



OUTDOOR	
WV-S65501-Z1, Z1G	White
WV-S65302-Z2, Z2G	White
WV-S65302-Z2-1	Black
WV-S65301-Z1, Z1G	White
WV-S65301-Z1-1	Black
WV-S65300-ZY, ZYG	White
WV-U65302-Z2, Z2G	White
WV-U65301-Z1, Z1G	White
WV-U65300-ZY, ZYG	White

SALT RESISTANT	
WV-S65301-Z1S	White

ACCESSORIES				
PICTURE	SKU DESCRIPTION	S65302, S65501, S65301 U65302, U65301	S65300 U65300	
	WV-QDC502G Smoke Dome	✓		
	WV-QDC502C Clear Dome	✓		
	WV-CW7S Smoke Dome		✓	
	WV-QDC504C Clear Dome		✓	
	WV-CW7SN Smoke Dome with ClearSight Coating		✓	
	WV-CW7CN Clear Dome with ClearSight Coating		✓	
	WV-QCA500A RJ45 Ethernet cable	✓*	✓	
	WV-QCA501A Multi cable (Ext I/O, Audio, DC)	✓	✓	

* Included in camera

Note

WALL/ POLE/ CORNER			 WV-QJB500-W WV-QJB500-B (If needed)	 FOR POLE WV-QPL500-W WV-QPL500-B	 FOR CORNER WV-QCN500-W WV-QCN500-B
			 WV-QWL501-W WV-QWL501-B	 FOR POLE WV-QPL500-W WV-QPL500-B	 FOR CORNER WV-QCN500-W WV-QCN500-B
HANGING		 WV-QSR501-W* WV-QSR501-B (4-screw)	 WV-QCL501-W WV-QCL501-B		
CEILING		 WV-QJB504-W WV-QJB501-W WV-QJB501-B (If needed)		 WV-Q105A (Indoor only. If needed.)	
RECESSED				WV-QEM504-W (for S65302/U65302) WV-QEM503-W (for S65501/S65301/U65301) WV-QEM502-W (for S65300/U65300) (Indoor only)	

*Other mounts to install with locally procured pipes/brackets are also available:
WV-QSR501F-W/WV-QSR501F-B (ISO Female), WV-QSR501M-W/WV-QSR501M-B (ISO Male),
WV-QSR501F1-W/WV-QSR501F1-B (ANSI Female), WV-QSR501M1-W/WV-QSR501M1-B (ISO Male)

INDOOR PTZ CAMERAS



INDOOR	
WV-S61702-Z3	White
WV-S61602-Z3	White
WV-S61302-Z4	White

ACCESSORIES		
PICTURE	SKU DESCRIPTION	ALL
	WV-QDC100G-W Smoke Dome	✓
	WV-QDC100C-W Clear Dome	✓

WALL/ POLE/ CORNER		WV-QWL100-W	FOR POLE WV-QPL500-W	FOR CORNER WV-QCN500-W
HANGING		WV-QCL100-W WV-QCL101-W	locally procured pipe	WV-QCL100-W, WV-QCL101-W (Indoor only. If needed.)
CEILING		WV-Q105A (Indoor only. If needed.)		
RECESSED		WV-QEM101-W		

INDOOR PTZ CAMERAS



INDOOR	
WV-S61501-Z1	White
WV-S61301-Z2	White
WV-U61301-Z2	White
WV-S61301-Z1	White
WV-S61300-ZY, ZYG	White
WV-U61301-Z1	White
WV-U61300-ZY, ZYG	White

ACCESSORIES			
PICTURE	SKU DESCRIPTION	S61501 S61301 U61301	S61300 U61300
	WV-QDC102C Clear Dome	✓	
	WV-CF5SA Smoke Dome		✓
	WV-QDC101C Clear Dome		✓
	WV-QAT100 Inner Cover	✓	

WALL/ POLE/ CORNER		WV-QWL500-W	WV-QJB500-W (If needed)	FOR POLE WV-QPL500-W
		Clear Dome	Smoke Dome	FOR CORNER WV-QCN500-W
HANGING		WV-QCL100-W WV-QCL101-W	locally procured pipe	WV-QCL100-W, WV-QCL101-W (Indoor only. If needed.)
CEILING		WV-Q105A (Indoor only. If needed.)		
		Clear Dome	Smoke Dome	S61501/S61301/U61301 only: WV-QCD100C-W Clear Dome WV-QCD100G-W Smoke Dome
RECESSED		Clear Dome	Smoke Dome	S61501/S61301/U61301 only: WV-QED100C-W Clear Dome WV-QED100G-W Smoke Dome
		S61300/U61300 only: WV-QEM501-W		

CORNER CAMERA

OUTDOOR

WV-X25580-F2LN2		Silver
ACCESSORIES		
PICTURE	SKU DESCRIPTION	ALL
	WV-QDC509CN Clear Dome with ClearSight Coating	✓
	WV-QCA501A Multi cable (Ext I/O, Audio, DC)	✓




OUTDOOR DOME CAMERAS

OUTDOOR

WV-X25700-V2LN, WV-X25600-V2LN WV-X25500-V3LN, WV-X25300-V3LN		White
WV-S25700-V2L, V2LN, V2LG WV-S25700-V2LN1		White Black
WV-S25600-V2L, V2LN, V2LG		White
WV-S25500-V3L, V3LN, V3LG, F6L, F3L WV-S25500-V3LN1		White Black
WV-S2536LA, LNA, LGA, LGNA WV-S2536LA, LTNA		White
WV-U2542LA, WV-U2532LA		White



ACCESSORIES			
PICTURE	SKU DESCRIPTION	OTHERS	U2542, U2532
	WV-CW7S Smoke Dome	✓	✓
	WV-QDC504C Clear Dome	✓	✓
	WV-CW7SN Smoke Dome with ClearSight Coating	✓	✓
	WV-CW7CN Clear Dome with ClearSight Coating	✓	✓
	WV-QCA500A RJ45 Ethernet cable	✓	
	WV-QCA501A Multi cable (Ext I/O, Audio, DC)	✓	



*Other mounts to install with locally procured pipes/brackets are also available:
WV-QSR501F-W/WV-QSR501F-B (ISO Female), WV-QSR501M-W/WV-QSR501M-B (ISO Male),
WV-QSR501F1-W/WV-QSR501F1-B (ANSI Female), WV-QSR501M1-W/WV-QSR501M1-B (ISO Male)

INDOOR DOME CAMERAS

INDOOR

WV-X22700-V2L, WV-X22600-V2L WV-X22500-V3L, WV-X22300-V3L		White
WV-S22700-V2L, V2LG WV-S22700-V2L1		White Black
WV-S22600-V2L, V2LG		White
WV-S22500-V3L, V3LG, F6L, F3L WV-S22500-V3L1		White Black
WV-S2236LA, LGA WV-S2236LA-B, LGA-B		White Black
WV-S2136LA, LGA WV-S2136LA-B, LGA-B		White Black
WV-S2136A, WV-S2136GA WV-S2136A-B, WV-S2136GA-B		White Black
WV-U2142LA, WV-U2132LA, WV-U21300-V2L		White



ACCESSORIES			
PICTURE	SKU DESCRIPTION	OTHERS	S2136, U2142, U2132, U21300
	WV-CR1S Smoke Dome	✓	
	WV-QDC200C Clear Dome	✓	
	WV-CF5SA Smoke Dome		✓
	WV-QDC101C Clear Dome		✓



COMPACT DOME CAMERAS

OUTDOOR

WV-U2540LA, U2530LA		White
WV-U2140LA, WV-U2130LA		White



ACCESSORIES		
PICTURE	SKU DESCRIPTION	ALL
	WV-QDC500S Smoke Dome	✓
	WV-QDC500C Clear Dome	✓



HIGH ZOOM
BULLET CAMERA

OUTDOOR

WV-X15701-Z3L, Z3LN	White
WV-X15502-Z1L, Z1LN	White
WV-X15501-Z3L, Z3LN	White
WV-X15501-Z1L, Z1LN	White
WV-X15302-Z1L, Z1LN	White
WV-X15301-Z1L, Z1LN	White
WV-S15701-Z3L, Z3LN	White
WV-S15501-Z3L, Z3LN	White
WV-S15501-Z1L, Z1LN	White
WV-S15301-Z1L, Z1LN	White

ACCESSORIES		
PICTURE	SKU DESCRIPTION	ALL
	WV-QCA500A RJ45 Ethernet cable	✓
	WV-QCA501A Multi cable (Ext I/O, Audio, DC)	✓

OUTDOOR
BULLET CAMERAS


OUTDOOR

WV-X15700-V2L, V2LN	White
WV-X15600-V2L, V2LN	
WV-X15500-V3L, V3LN	
WV-X15300-V3L, V3LN	
WV-S15700-V2L, V2LN	White
WV-S15600-V2L, V2LN	White
WV-S15500-V3L, V3LN , F6L, F3L	White
WV-S15500-V3LN1	Black
WV-S1536LA, LNA, LTA, LTNA	White
WV-S1536LA-B, LNA-B	Black
WV-U1542LA, WV-U1532LA	White

SALT RESISTANT

WV-S15700-V2LK	White
WV-S15500-V3LK	White
WV-S1536LNSA	White

ACCESSORIES			
PICTURE	SKU DESCRIPTION	OTHERS	U1542, U1532
	WV-QCA500A RJ45 Ethernet cable	✓	
	WV-QCA501A Multi cable (Ext I/O, Audio, DC)	✓	



INDOOR
BOX CAMERAS

INDOOR

WV-S1136A	White
WV-U1142A, U11300-V2, U1132A	White
WV-U1130A	White

OUTDOOR
FISHEYE
CAMERAS

OUTDOOR


WV-S4576LA, LMA	White
WV-S4556LA, LMA	White

ACCESSORIES		
PICTURE	SKU DESCRIPTION	ALL
	WV-QDC507C Clear Dome	✓


INDOOR
FISHEYE
CAMERAS

INDOOR

WV-S4176A	White
WV-S4156A	White



*Other mounts to install with locally procured pipes/brackets are also available:
WV-QSR501F-W (ISO Female), WV-QSR501M-W (ISO Male),
WV-QSR501F1-W (ANSI Female), WV-QSR501M1-W (ISO Male)



COMPACT DOME CAMERAS



OUTDOOR


WV-X35402-F2L, F2LM WV-X35302-F2L, F2LM	White
WV-S35402-F2L, F2LG WV-S35302-F2L, F2LG	White
WV-S35402-F2L1 WV-S35302-F2L1	Black
WV-U35401-F2L, F2LG WV-U35301-F2L, F2LG	White

INDOOR

WV-S32402-F2L, F2LG WV-S32302-F2L, F2LG	White
WV-S32402-F2L1 WV-S32302-F2L1	Black
WV-U31401-F2L, F2LG WV-U31301-F2L, F2LG	White

ACCESSORIES

PICTURE	SKU DESCRIPTION	ALL
	WV-CW6SA Smoke Dome	☒
	WV-QDC505C Clear Dome	☒

ON-VEHICLE
CAMERA

OUTDOOR

WV-SBV131M	Gray
------------	------

ACCESSORIES


PICTURE	SKU DESCRIPTION	SBV131M
	WV-QDC506C Clear Dome	

Direct mount only

INDOOR COMPACT CAMERA

**INDOOR**

WV-S71300A-F3	White
---------------	-------



Note

[illegible]

Trademarks and registered trademarks

- HDMI, the HDMI logo and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing, LLC.
- ONVIF is a trademark of ONVIF, Inc.
- GlobalSign and the GlobalSign Logo are registered trademarks of GMO GlobalSign K.K.
- The SD, SDHC, miniSDHC, microSDHC, SDXC and microSDXC Logos are trademarks of SD-3C LLC.
- iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries.
- Android is a trademark of Google LLC.
- All other trademarks identified herein are the property of their respective owners.

Important

- Safety Precautions : Carefully read the Basic Information, Installation Guide and Operating Instructions before using this product.
- i-PRO Co., Ltd. cannot be held responsible for the performance of the network and/or other manufacturers' products used on the network.
- The same catalog is provided for all countries. Some accessories may not be available in some countries.

Security Cautions

- When using the products in this catalog, take appropriate measures to avoid the following security breaches:
 - Disclosure of private information via the products.
 - Unauthorized use of products by a third party.
 - Interference or suspension of use of products by third party.
 - All pictures are simulated.
 - Design and specifications are subject to change without notice.



i-PRO Co., Ltd.

https://i-pro.com/products_and_solutions/surveillance

(2B-017KA)